



APC Rack PDU 9000 Switched, ZeroU, 16A, 230V, (21) C13 & (3) C19, IEC309 Cord

New

APDU9959EU3

Call for More Information 0800 2799254

- Includes: Installation guide, Locking input power cord, Rack mounting brackets, Safety guide

Output	
Nominal Output Voltage	230V
Overload Protection	No
Maximum Total Current Draw	16
Output Connections	(21) IEC 60320 C13 (3) IEC 60320 C19

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz
Input Connections	IEC 60309 16 A 2P + E, IEC 60320 C20
Cord Length	3meters
Acceptable Input Voltage	220 - 240VAC
Number of Power Cords	1
Load Capacity	3700VA
Maximum Input Current	16A
Maximum Line Current	16A

Physical	
Maximum Height	1794MM, 179.4CM
Maximum Width	55MM, 5.5CM
Maximum Depth	46MM, 4.6CM
Net Weight	5.61KG

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Shipping weight	8.59KG
Shipping Height	2002MM, 200.2CM
Shipping Width	165MM, 16.5CM
Shipping Depth	114MM, 11.4CM
Color	Black
Units per Pallet	48.0

Environmental	
Operating Temperature	-5 - 60 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	EAC, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC part 15 class A, ICES-003, RCM, VDE
Standard warranty	3 years repair or replace

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.