

Technical Specifications

APC Power-Saving Back-UPS Pro 1200, 230V, CEE 7/5 | BR1200G-FR | Downloaded on 11/08/2021 (EST)



APC Power-Saving Back-UPS Pro 1200, 230V, CEE 7/5

BR1200G-FR

Call for More Information +32(0)23737502

- Includes: Telephone cable, USB cable, User manual

Output

Output power capacity	720 Watts / 1.2kVA
Max Configurable Power (Watts)	720 Watts / 1.2kVA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Output Connections	(3) French/Belgian (3) French/Belgian
Transfer Time	10 ms typical : 12 ms maximum

Input


Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input Connections	French/Belgian
Cord Length	1.5meters
Input voltage range for main operations	156 - 300 Adjustable, 176 - 294V
Number of Power Cords	1

Batteries & Runtime

Battery type	Lead-acid battery
Typical recharge time	8hour(s)
Nominal Battery Voltage	24 V

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Batteries & Runtime	
Replacement Battery	APCRBC124 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	23 Watts
Runtime	View Runtime Graph (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	Optional Simple Signalling RS232 cable, USB
Control panel	Multifunction LCD status and control console

Surge Protection and Filtering	
Surge energy rating	441Joules
Data Line Protection	RJ11 analog phone line for phone/fax/modem/DSL, RJ45 network line - 10/100/1000 Base-T Ethernet

Physical	
Maximum Height	301MM, 30.1CM
Maximum Width	112MM, 11.2CM
Maximum Depth	380MM, 38.0CM
Net Weight	11.6KG
Shipping weight	13.2KG
Shipping Height	387MM, 38.7CM
Shipping Width	238MM, 23.8CM
Shipping Depth	488MM, 48.8CM
Master Carton Units	1.0
Master Carton Weight	27.67
Units per Pallet	16.0
SCC Codes	10731304268724

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 9144meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	45.0dBA

Conformance	
Approvals	CE
Equipment protection policy	Lifetime : 150000 euros
Standard warranty	2 years repair or replace, 3 years repair or replace for European Union countries

Sustainable Offer Status	
RoHS	Compliant
PEP	Available in Documentation tab
EOLI	Available in Documentation tab

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.