



## EasyPDU, Basic, 1U, 10A, 230V, 6SCH,1C13

## EPDU1010B-SCH

Call for More Information 0800 2799254

• Includes: Installation guide, Rack mounting brackets, Toolless mounting kit

Output	
Other Output Voltages	200, -, 240 V

Input	
Input frequency	50/60 Hz
Input Connections	IEC 320 C14 10 A
Cord Length	2.5meters
Number of Power Cords	1
Load Capacity	2300VA
Maximum Input Current	10A

Physical	
Maximum Height	44MM, 4.44CM
Maximum Width	482MM, 48.2CM
Maximum Depth	44MM, 4.44CM
Rack Height	1U
Net Weight	0.6KG
Shipping weight	1.1KG
Shipping Height	150MM, 15.0CM
Shipping Width	560MM, 56.0CM
Shipping Depth	80MM, 8.0CM
Color	Black

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## **Technical Specifications**



EasyPDU, Basic, 1U, 10A, 230V, 6SCH,1C13 | EPDU1010B-SCH | Downloaded on 02/25/2022 (EST)

Environmental	
Operating Temperature	-5 - 45 °C
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CE

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.