



Easy PDU, Basic, 1U, 16A, 230V, (8)C13

New

EPDU1016B

Call for More Information 0800 2799254

- Includes: Cable, Installation guide, Rack mounting brackets, User manual

Output

Nominal Output Voltage	208V, 230V
Maximum Total Current Draw	16
Output Connections	(8) IEC 60320 C13

Input

Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60320 C20
Cord Length	2.5meters
Load Capacity	3680VA
Maximum Input Current	16A

Physical

Maximum Height	44MM, 4.44CM
Maximum Width	482MM, 48.2CM
Maximum Depth	44MM, 4.44CM
Rack Height	1U
Net Weight	0.58KG
Shipping weight	1.18KG
Shipping Height	150MM, 15.0CM
Shipping Width	560MM, 56.0CM
Shipping Depth	80MM, 8.0CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Easy PDU, Basic, 1U, 16A, 230V, (8)C13 | EPDU1016B | Downloaded on 02/25/2022 (EST)

Physical	
Color	Black

Environmental	
Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CE, TÜV
Standard warranty	1 year repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.