



## Easy PDU, Metered, 1U, 16A, 230V, (8)C13

New

EPDU1016M

Call for More Information 0800 2799254

- Includes: Cable, Horizontal mounting brackets, Installation guide, User manual

Output	
Nominal Output Voltage	208V, 230V
Maximum Total Current Draw	16
Output Connections	(8) IEC 60320 C13

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60320 C20
Cord Length	2.5meters
Load Capacity	3680VA
Maximum Input Current	16A

Physical	
Maximum Height	44MM, 4.44CM
Maximum Width	482MM, 48.2CM
Maximum Depth	44MM, 4.4CM
Rack Height	1U
Net Weight	0.7KG
Shipping weight	1.4KG
Shipping Height	80MM, 8.0CM
Shipping Width	560MM, 56.0CM
Shipping Depth	150MM, 15.0CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Easy PDU, Metered, 1U, 16A, 230V, (8)C13 | EPDU1016M | Downloaded on 02/25/2022 (EST)

### Physical

Color	Black
-------	-------

### Environmental

Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

### Conformance

Approvals	CE, TÜV
Standard warranty	1 year repair or replace

### Sustainable Offer Status

RoHS	Compliant
------	-----------

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.