



Easy PDU,Basic,ZeroU,16A,230V,(14) SCHUKO

New

EPDU1116B-SCH

Call for More Information 0800 2799254

- Includes: Installation guide, Toolless mounting kit, Vertical mounting brackets

Output	
Nominal Output Voltage	230V
Maximum Total Current Draw	16
Output Connections	(14) Schuko CEE 7

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	Schuko CEE 7 / EU1-16P
Cord Length	3meters
Number of Power Cords	1
Load Capacity	3680VA
Maximum Input Current	16A

Physical	
Maximum Height	902MM, 90.2CM
Maximum Width	62MM, 6.2CM
Maximum Depth	44MM, 4.44CM
Net Weight	1.94KG
Shipping weight	2.84KG
Shipping Height	1320MM, 132.0CM
Shipping Width	160MM, 16.0CM
Shipping Depth	110MM, 11.0CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical

Color	Black
-------	-------

Environmental

Operating Temperature	-5 - 45 °C
-----------------------	------------

Operating Relative Humidity	5 - 95 %
-----------------------------	----------

Operating Elevation	0 - 3048meters
---------------------	----------------

Storage Temperature	-25 - 65 °C
---------------------	-------------

Storage Relative Humidity	5 - 95 %
---------------------------	----------

Storage Elevation	0 - 15240meters
-------------------	-----------------

Conformance

Approvals	CE, TÜV
-----------	---------

Standard warranty	1 year repair or replace
-------------------	--------------------------

Sustainable Offer Status

RoHS	Compliant
------	-----------