



## Easy PDU,Basic,ZeroU,16A,230V,(20)C13 & (4)C19; IEC309

New

EPDU1116B

Call for More Information 0800 2799254

- Includes: Installation guide, Toolless mounting kit, Vertical mounting brackets

Output	
Nominal Output Voltage	230V
Maximum Total Current Draw	16
Output Connections	(20) IEC 60320 C13 (4) IEC 60320 C19

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60309 16 A 2P + E
Cord Length	3meters
Number of Power Cords	1
Load Capacity	3680VA
Maximum Input Current	16A

Physical	
Maximum Height	902MM, 90.2CM
Maximum Width	62MM, 6.2CM
Maximum Depth	44MM, 4.44CM
Net Weight	2.2KG
Shipping weight	2.98KG
Shipping Height	1320MM, 132.0CM
Shipping Width	160MM, 16.0CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Physical	
Shipping Depth	110MM, 11.0CM
Color	Black

  

Environmental	
Operating Temperature	0 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

  

Conformance	
Approvals	CE, TÜV
Standard warranty	1 year repair or replace

  

Sustainable Offer Status	
RoHS	Compliant

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.