



## Easy PDU,Metered,ZeroU,16A,230V,(18)C13 & (3)C19; IEC309

New

EPDU1116M

Call for More Information 0800 2799254

- Includes: Installation guide, User manual, Vertical mounting brackets

| Output                     |   |
|----------------------------|---|
| Nominal Output Voltage     | 230V                                    |
| Maximum Total Current Draw | 16                                      |
| Output Connections         | (3) IEC 60320 C19<br>(18) IEC 60320 C13 |

| Input                 |                       |
|-----------------------|-----------------------|
| Nominal Input Voltage | 200V, 208V, 230V      |
| Input frequency       | 50/60 Hz              |
| Input Connections     | IEC 60309 16 A 2P + E |
| Cord Length           | 3meters               |
| Number of Power Cords | 1                     |
| Load Capacity         | 3680VA                |
| Maximum Input Current | 16A                   |

| Physical        |                 |
|-----------------|-----------------|
| Maximum Height  | 902MM, 90.2CM   |
| Maximum Width   | 62MM, 6.2CM     |
| Maximum Depth   | 44MM, 4.44CM    |
| Net Weight      | 2.5KG           |
| Shipping weight | 3.0KG           |
| Shipping Height | 1320MM, 132.0CM |
| Shipping Width  | 160MM, 16.0CM   |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Easy PDU,Metered,ZeroU,16A,230V,(18)C13 & (3)C19; IEC309 | EPDU1116M | Downloaded on 02/25/2022 (EST)

| Physical       |               |
|----------------|---------------|
| Shipping Depth | 110MM, 11.0CM |
| Color          | Black         |

| Environmental               |                 |
|-----------------------------|-----------------|
| Operating Temperature       | -5 - 45 °C      |
| Operating Relative Humidity | 5 - 95 %        |
| Operating Elevation         | 0 - 3048meters  |
| Storage Temperature         | -25 - 65 °C     |
| Storage Relative Humidity   | 5 - 95 %        |
| Storage Elevation           | 0 - 15240meters |

| Conformance       |                          |
|-------------------|--------------------------|
| Approvals         | CE, TÜV                  |
| Standard warranty | 1 year repair or replace |

| Sustainable Offer Status |           |
|--------------------------|-----------|
| RoHS                     | Compliant |

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.