



Easy PDU, Switched,ZeroU,16A,230V,(20)C13 & (4)C19, IEC309

EPDU1116S

Call for More Information 0800 2799254

- Includes: Installation guide, User manual, Vertical mounting brackets

Output	
Nominal Output Voltage	230V
Maximum Total Current Draw	16
Output Connections	(4) IEC 60320 C19 (20) IEC 60320 C13

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60309 16 A 2P + E
Cord Length	3meters
Number of Power Cords	1
Load Capacity	3680VA
Maximum Input Current	16A

Physical	
Maximum Height	1738MM, 173.8CM
Maximum Width	55MM, 5.5CM
Maximum Depth	62MM, 6.2CM
Net Weight	7.3KG
Shipping weight	8.5KG
Shipping Height	1950MM, 195.0CM
Shipping Width	160MM, 16.0CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Easy PDU, Switched,ZeroU,16A,230V,(20)C13 & (4)C19, IEC309 | EPDU1116S | Downloaded on 02/25/2022 (EST)

Physical	
Shipping Depth	110MM, 11.0CM
Color	Black

Environmental	
Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CE, EAC, TÜV
Standard warranty	1 year repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.