



## Easy PDU, Metered, Zero U, 32A, 230V, (20)C13 & (4)C19 ; IEC309

New

EPDU1132M

Call for More Information 0800 2799254

- Includes: Installation guide, Toolless mounting kit, User manual, Vertical mounting brackets

### Output

Nominal Output Voltage	230V
Maximum Total Current Draw	32
Output Connections	(20) IEC 60320 C13 (4) IEC 60320 C19

### Input

Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60309 32 A 2P + E
Cord Length	3meters
Acceptable Input Voltage	220 - 240VAC
Number of Power Cords	1
Load Capacity	7360VA
Maximum Input Current	32A
Maximum Line Current	32A

### Physical

Maximum Height	1175MM, 117.5CM
Maximum Width	62MM, 6.2CM
Maximum Depth	44MM, 4.44CM
Net Weight	3.72KG
Shipping weight	4.48KG

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Easy PDU, Metered, Zero U, 32A, 230V, (20)C13 & (4)C19 ; IEC309 | EPDU1132M | Downloaded on 02/25/2022 (EST)

Physical	
Shipping Height	1320MM, 132.0CM
Shipping Width	160MM, 16.0CM
Shipping Depth	110MM, 11.0CM
Color	Black

Environmental	
Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CE, EAC, RCM, TÜV
Standard warranty	1 year repair or replace

Sustainable Offer Status	
RoHS	Compliant

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.