



Easy PDU, Metered, Zero U, 22 kW, 230V, (18) C13 & (6) C19;IEC309

EPDU1232M

Call for More Information 0800 2799254

- Includes: Installation guide, Toolless mounting kit, Vertical mounting brackets

Output	
Nominal Output Voltage	230V
Maximum Total Current Draw	32
Output Connections	(18) IEC 60320 C13 (6) IEC 60320 C19

Input	
Nominal Input Voltage	400V 3PH
Input frequency	50/60 Hz
Input Connections	IEC 60309 32 A 3P + N + PE
Cord Length	2meters
Number of Power Cords	1
Load Capacity	22000VA
Maximum Input Current	32A

Physical	
Maximum Height	1506MM, 150.6CM
Maximum Width	62MM, 6.2CM
Maximum Depth	44MM, 4.44CM
Net Weight	4.64KG
Shipping weight	5.48KG
Shipping Height	1660MM, 166.0CM
Shipping Width	160MM, 16.0CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Easy PDU, Metered, Zero U, 22 kW, 230V, (18) C13 & (6) C19;IEC309 | EPDU1232M | Downloaded on 02/25/2022 (EST)

Physical	
Shipping Depth	110MM, 11.0CM
Color	Black

Environmental	
Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CE, EAC, RCM, TÜV
Standard warranty	1 year repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.