#### **Stripping Tool** for coax cables

16 60





Article No.	EAN 4003773-	<b>←→</b> mm		Stripping capacities Ø mm	Δ <b>΄</b> Δ g
16 60 100 SB	040811	100	MM	Coax-cables 4.8 - 7.5 mm round cables 3 x 0,75 mm <sup>2</sup>	22

- > for dismantling and stripping all common coax cables between 4.8 - 7.5 mm dia. (e.g. for TV- and satellite antenna), also suitable for PVC round cable 3 x 0.75 mm<sup>2</sup>
- > with length scale 5.0 20.0 mm
- > double shell, folding back stripping tool
- > with opening spring and locking device
- > body: plastic, fibreglass-reinforced



## **Dismantling Tool** for flat and round cables







- > for flat cables up to 12 mm in width
- > for dismantling and stripping all common round and damp-proof installation cables Ø 4.0 to 13.0 mm (e.g. NYM cable 3 x 1.5 mm<sup>2</sup> up to 5 x 2.5 mm<sup>2</sup>)
- > stripping device for cross-sections 0.8 / 1.5 / 2.5 mm<sup>2</sup> (AWG 20 / 16 / 14)
- > with opening spring and locking device
- > for use in confined and difficult to access work areas
- > also for use in conduit and distribution boxes
- > body: plastic, fibreglass-reinforced



	EAN	4>		Stripping	capacities		77
Article No.	4003773-	mm		Ø mm	mm²	Types of cables	g
16 64 125 SB	076933	125	•••••••• WM	4.0 - 13.0	0.8 - 2.5	flat cable 12 mm / round cable Ø 4 - 13 mm	48

### Dismantling Tool for data cables

16 65



- > for stripping UTP and STP data cables with diameters of 4.5 to 10.0 mm
- > stripping device for cross-sections 0.2 / 0.3 / 0.8 / 1.5 / 2.5 / 4 mm<sup>2</sup>
- > double shell, folding back stripping tool
- > with opening spring and locking device
- > practical clip for easy transport
- > body: plastic, fibreglass-reinforced
- > blades: special tool steel, oil-hardened, TiN-coated

16 65 125 SB WW



	EAN	<b>←→</b>		Stripping	capacities		47
Article No.	4003773-	mm		Ø mm	mm <sup>2</sup>	Types of cables	g
16 65 125 SB	043157	125	MM	4.5 - 10.0	0.2 - 4	CAT 5, CAT 6, CAT 7, Twisted-Pair (UTP/STP)	50

# **Universal Dismantling Tools**

16

- > for dismantling and stripping all common round and damp-proof installation cables between 8 - 13 mm dia. (e.g. 3 x 1.5 mm<sup>2</sup> up to 5 x 2.5 mm<sup>2</sup>)
- > also for use in conduit and distribution boxes
- > double shell, folding back stripping tool
- > with opening spring and locking device
- > practical clip for easy transport
- > body: plastic, fibreglass-reinforced

#### 16 85 125 SB

with additional blade for longitudinal cuts; telescopic blade inside; stripping device for cross-sections 0.2 / 0.3 / 0.8 / 1.5 / 2.5 / 4 mm<sup>2</sup>; with integrated cable guide for longitudinal cut. This enables rigid insulation (e.g. halogen-free) to be stripped more easily.









16 85 125 SB WW

	EAN	4>		Stripping capacities			7,7
Article No.	4003773-	mm		Ø mm	mm²	Types of cables	g
16 80 125 SB	040828	125	WW	8.0 - 13.0		round cable, e.g.: 3 x 1.5 mm² up to 5 x 2.5 mm²	71
16 85 125 SB	060444	125	WM	8.0 - 13.0	0.2 - 4.0	round cable, e.g.: 3 x 1.5 mm² up to 5 x 2.5 mm²	67

16

90

# **Universal Dismantling Tool**

for building and industrial cables





- > for dismantling and stripping all common round and damp-proof installation cables between 8.0 - 13.0 mm dia. (e.g.  $3 \times 1.5 \text{ mm}^2 \text{ up to } 5 \times 2.5 \text{ mm}^2$ )
- > specially suitable for larger cross-sections and for difficult insulating materials
- > no adjustment of blades to cutting depth required
- > with opening spring and locking device
- > stripping device for conductors and strands 1.5 mm<sup>2</sup> and 2.5 mm<sup>2</sup>
- > two-way length stop (ideal for right and left-handers)
- > fastening device on the end of the handle (fall protection)
- > for use in confined and difficult to access work areas
- > also for use in conduit and distribution boxes
- > body: plastic, fibreglass-reinforced



16 90 130 SB WW

	EAN	4>		Stripping	capacities		7,7
Article No.	4003773-	mm		Ø mm	mm <sup>2</sup>	Types of cables	g
16 90 130 SB	076940	130	WW	8.0 - 13.0	1.5 + 2.5	round cable, e.g. 3 x 1.5 mm <sup>2</sup> up to 5 x 2.5 mm <sup>2</sup>	47