

USB-C to VGA and HDMI Adapter - 2-in-1 - 4K 30Hz - Space Grey

**Product ID:** CDP2HDVGA



This USB-C to VGA and HDMI adapter offers a portable solution for connecting your USB Type-C laptop to a VGA or HDMI display. The multiport video adapter also works as a splitter, enabling you to simultaneously output an identical video signal to two separate monitors (1 x HDMI and 1 x VGA).

Avoid the hassle of carrying different adapters, with a 2-in-1 USB-C monitor adapter. With VGA, and HDMI outputs, you can conveniently connect your laptop to any HDMI or VGA-equipped display, using this multiport adapter.

The adapter features a durable aluminum enclosure and can withstand being carried in your travel bag.

The HDMI output on this USB-C video adapter supports UHD resolutions up to 4K 30Hz, while the VGA output supports HD resolutions up to 1920 x 1200.

The USB-C video adapter has a Space Gray housing and built-in USB-C cable designed to match your Space Gray MacBook or MacBook Pro. The adapter is compatible with USB-C DP Alt Mode devices.

CDP2HDVGA is backed by a StarTech.com 3-year warranty and free lifetime technical support.

## Certifications, Reports and Compatibility

### Applications

- Connect to virtually any VGA or HDMI display while traveling
- Use as a video splitter to output an identical image to a VGA and HDMI monitor simultaneously splitting the image
- Output video to a secondary VGA, or HDMI monitor

## Features

- Maximize your laptop's video compatibility with a 2-in-1 adapter: USB-C to HDMI and VGA
- Support resource-demanding applications with UHD resolutions up to 4K 30Hz
- Space Gray adapter matches your Space Gray MacBook or MacBook Pro

---

### Prominence

Warranty	3 Years
Description CDW 75 - 1st Line	StarTech.com USB C to VGA and HDMI Adapter - Aluminum - USB-C Multiport

---

### Hardware

Active or Passive Adapter	Active
AV Input	USB-C
AV Output	HDMI - 1.4 VGA
Chipset ID	ITE - IT6222

---

### Performance

Video Revision	HDMI 2.0
Maximum Cable Distance To Display	49.9 ft [15.2 m]
Maximum Analog Resolutions	1920 x 1200 @ 60Hz (VGA)
Maximum Digital Resolutions	3840 x 2160 @ 30Hz (HDMI)
Supported Resolutions	Maximum HDMI output:3840 x 2160 @ 30Hz  Maximum VGA output: 1920 x 1200 @ 60Hz  <i>Lower resolutions and refresh rates may also be supported</i>
Audio Specifications	HDMI - 7.1 Channel Audio
MTBF	1,576,016 hours

---

**Connector(s)**

Connector A	USB-C (24 pin) DisplayPort Alt Mode
Connector B	VGA (15 pin, High Density D-Sub)
	HDMI (19 pin)

---

**Special Notes / Requirements**

Note	HDMI and VGA can output video at the same time. If both video outputs are connected, they'll display the same image at a maximum resolution of 1920x1200 @ 60Hz
	Maximum Cable Distance to Display refers to digital video. VGA distance capabilities are dependent upon the quality of your cabling

---

**Environmental**

Operating Temperature	0C to 45C (32F to 113F)
Storage Temperature	-10C to 70C (14F to 158F)
Humidity	5~90% RH

---

**Physical Characteristics**

Color	Space Gray
Accent Color	Black
Material	Aluminum
Cable Length	6.6 in [16.7 cm]
Product Length	8.1 in [20.5 cm]
Product Width	2.4 in [62.0 mm]
Product Height	0.6 in [15.0 mm]
Weight of Product	1.5 oz [43.0 g]

---

**Packaging Information**

Package Length	7.0 in [17.9 cm]
Package Width	3.1 in [80.0 mm]
Package Height	0.8 in [20.0 mm]



Shipping (Package) Weight	2.2 oz [62.0 g]
------------------------------	-----------------

---

**What's in the  
Box**

Included in Package	Travel A/V Adapter
---------------------	--------------------

---

***\*Product appearance and specifications are subject to change without notice.***

