


# CLIFF

## SLIM CAT5e RJ45 SHIELDED FRONT MOUNTING FEEDTHROUGH CONNECTOR



### Part No.

- CP30620S** SLIM FM Cat5e RJ45 Shielded Black plastic frame, CSK holes
- CP30620SX** SLIM FM Cat5e RJ45 Shielded Black plastic frame, Ø2.5 PLAIN holes
- CP30620SX1** SLIM FM Cat5e RJ45 Shielded Black plastic frame, Ø3.2 PLAIN holes

### Feedthrough Features

- Fits standard rectangular cutout.
- Various hole mounting options.
- No soldering or punch termination. Use standard cable for each connector style.
- Low rear profile.

### General:

Please note: Functionality is affected by cable quality, length and cable wiring configuration.

### Material:

1. RJ45 In-Line Coupler: PC/ABS, UL 94V-0
2. RJ45 In-Line Coupler Contact: Phosphor Bronze, 3-50 micro inches gold plating over nickel plate.
3. PCB: FR4, UL 94V-0
4. Plastic Frame: Polyamide UL94 V-2

### Performance:

1. T568A & T568B wiring.
2. Meet ISO/IEC 11801 and EN50173
3. Meet ANSI/TIA/EIA 568B.2
4. Operating temperature: Min -10°C Max +70°C