

DIGITUS Wall Mounting Cabinets - SoHo, Slim

DN-19 04U-PB EAN 4016032200109





Wall mounting cabinet, SOHO, slim, 145x525x475 mm 3U rotatable, 2U fix, color grey (RAL 7035)

The Wall Mounting Cabinets SoHo, Slim are perfect for the placing of active and passive components. They are characterized by an easy and time saving installation. The modern design suits to every office or home environment. There are two separate installation possibilities: The front side is equipped with a rotatable vertical 3U rail. Alternatively, it can be positioned horizontally or even angled. On the rear side there is a 2U rail (fixed), which can be used for passive network components for example. Due to punched out mounting holes in the lower housing area also non rack mountable equipment can be installed (e.g. DSL router, etc.). Alternatively you can install a device mounting plate which is available seperately.

The DIGITUS® Professional Wall Mounting Cabinets are made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany

- Safety class rating IP20
- Lockable housing with transparent polycarbonat window
- Upper part of housing can opened up to 80°
- Door stop mechanism of steel which keeps the door open
- 1-point-locking-mechanism
- 2 separate 483 mm (19") mounting options: 3U vertical (rotatable), 2U horizontal (fix)

- max. installation depth (from front vertical rail to rear horizontal rail): ca. 265 mm
- 2.0 mm strong sheet steel with a high loading capacity, powder coated
- · Pre-punched knock-outs for cable management
- Ventilation slots for active and passive ventilation and exhausting
- Cable tire-up divisions
- Lower housing area with punched out mounting holes for the installation of equipment which is not suitable for 483 mm (19") mounting
- Mounting plate is optional available
- Dimensions ventilator mount: 57.5 x 57.5 mm
- Hole distances ventilator installation: 50 x 50 mm (3.5 mm diameter)
- · IP protection class: IP20
- Color: light grey, RAL 7035
- Depth: 475 mm
- Front door: Glass door, single opening
- Units: 5
- Load capacity: 30 kg
- Mounted: yes
- Cabinet type: Wall mounting cabinet, home automation
- Width: 525 mm

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	9.50	50.00	53.00	16.00	42,400.00
Packaging Unit Inside	1	9.50	50.00	53.00	16.00	42,400.00
Packaging Unit Single	1	9.50	50.00	53.00	16.00	42,400.00
Net single without Packaging	1	8.78	50.00	53.00	16.00	42,400.00



More images:

