

# DIGITUS aluminum outlet strip with pre-fuse, 8 safety outlets, 2 m supply IEC C14 plug

DN-95410-R  
EAN 4016032369721



### 1U Aluminum PDU, rackmountable, 8x red CEE 7/7 10A Plug, 250VAC 50/60Hz, outlet

The DIGITUS® power distribution units are the perfect solution for you 482.6 mm (19") network- or server cabinet. Optimized for rack installation with 220-240V 50-60 Hz the DIGITUS® PDU offer you the best performance with qualified efficiency. The 482.6 mm (19") fixing material provides an optimized enclosing on the profile rails of your cabinets. Every PDU can be mounted horizontally as well as vertically and has the possibility, according to the cabinet, to be mounted faced up or down.

#### Safe and professional power in the 482.6 mm (19") range

- 8x RED Socket outlets 250VAC 50/60Hz / 10A / 2500W

- Aluminum profile
- 35° turned outlets
- 2 metal fixings included
- Cable: 2 m H05VV-F 3G1,5 mm<sup>2</sup>
- IEC C14, plug
- Pre-fuse
- 35° turned safety outlets
- Inch form factor (IEC 60297): 482.6 mm (19")
- Installation: Rack 1U
- Outlets: Schuko CEE 7/3
- Phase: 1ph
- Volts: 230 V

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	10	9.64	53.00	28.50	25.00	37,762.50
Packaging Unit Inside	1	0.96	50.10	11.00	5.00	2,755.50
Packaging Unit Single	1	0.96	50.10	11.00	5.00	2,755.50
Net single without Packaging	1	0.86	50.10	11.00	5.00	2,755.50

#### More images:

