

# DIGITUS VGA Splitter 500MHz, 4-Port

DS-42110  
EAN 4016032323815



### Video Splitter 1 PC, 4 Monitors 500 MHz,HDSUB 15/F - 4xHDSUB 15/F, Max. 2048x1536p

With a video splitter you can use one video source to display identical images on 2, 4, 8, or 16 monitors - or on even more screens by means of cascading. Thus, a video splitter can be used in various application fields, e.g. test bench facilities, data centers, help desks, video broadcasting, presentations and educational facilities.

#### Provides simultaneous display on four different monitors - Perfect for classrooms, tradeshow, or in-store displays!

- Enables to split a video-signal from a PC onto 4 monitors, or other video output devices
- Video bandwidth: 500MHz
- Max. resolution: 2048x1536p @60Hz
- Max. transmission distance: 75m

- Cascadable (max. 64)
- Metal housing for better EMI shielding
- DDC, DDC2, DDC2B support
- Video IN/OUT: HD DSUB, 15-pin, jacks
- Number of ports: 4
- HDTV Resolution max.: 2048 x 1536 Pixel, 60Hz
- HDTV Standard: Full HD
- Signal input: VGA
- Signal output: VGA

#### Package contents

- VGA splitter 500MHz, 4-port
- Power supply
- Manual

### Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	10	7.50	32.00	27.00	32.50	28,080.00
Packaging Unit Inside	1	0.75	6.00	25.00	15.00	2,250.00
Packaging Unit Single	1	0.75	6.00	25.00	15.00	2,250.00
Net single without Packaging	1	0.63	6.00	25.00	15.00	2,250.00

### More images:



