
(LLE2050APVT5)



KEMET, FLLE2-PV, EMI/RFI Filters, Noise Suppression, 1.2 kV, 50 A, 170x95x80mm



Dimensions		
L	170mm NOM	
W	95mm NOM	
Н	80mm NOM	
L1	200mm NOM	
L2	183mm NOM	
W1	60mm NOM	
W2	75mm NOM	
К	6.5mm NOM	
M (Earth)	Threaded Studs M6	

Packaging Specifications		
Packaging:	Bulk	
Packaging Quantity:	1	
Component Weight:	1.8 kg	

General Information		
Series:	FLLE2-PV	
Style:	Chassis Mount	
Description:	EMI Filter, With Y Capacitor	
Features:	Single Phase, Photovoltaic Applications	
Phase:	Single-phase	
RoHS:	Yes	
Qualifications:	IEC/EN 60939, UL 1283	
Terminal Type:	Threaded Studs M6	

Specifications		
Voltage DC:	1200 VDC	
Rated Current:	50 A (50°C)	
Rated Temperature:	55°C	
Temperature Range:	-40/+100°C	
Climate Category:	40/100/21	
Test Voltage DC (P to P):	1300 VDC	
Test Voltage DC (P to E):	1300 VDC	
Power Loss:	6 W (25°C 50 Hz)	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

