

# Fuses 6.3 x 32

## Fuses, Fast-blow, Ceramic



Excellent I<sup>2</sup>T characteristics

Welded element for enhanced vibration tolerance

Ceramic cartridge, nickel plated brass end caps

UL approved, E492698

### SPECIFICATION:

Characteristic (time/current)	Fast-blow
Rated voltage	250 VAC
Construction form	Ceramic tube
Dimensions $\phi \times L$	6.3 x 32 mm

### PRODUCT RANGE:

Art. Nr.	Rated current	Breaking capacity
RND 170-00140	0.5 A	35 A@ 250 VAC
RND 170-00142	0.63 A	35 A@ 250 VAC
RND 170-00143	0.75 A	35 A@ 250 VAC
RND 170-00145	0.8 A	35 A@ 250 VAC
RND 170-00127	1 A	100 A@ 250 VAC
RND 170-00128	1.25 A	100 A@ 250 VAC
RND 170-00129	1.5 A	100 A@ 250 VAC
RND 170-00133	2 A	100 A@ 250 VAC
RND 170-00134	2.5 A	100 A@ 250 VAC
RND 170-00137	3.15 A	100 A@ 250 VAC
RND 170-00138	4 A	200 A@ 250 VAC
RND 170-00139	5 A	200 A@ 250 VAC
RND 170-00141	6 A	200 A@ 250 VAC
RND 170-00144	8 A	200 A@ 250 VAC
RND 170-00130	10 A	200 A@ 250 VAC
RND 170-00131	15 A	200 A@ 250 VAC
RND 170-00132	16 A	200 A@ 250 VAC
RND 170-00135	20 A	200 A@ 250 VAC
RND 170-00136	25 A	200 A@ 250 VAC