

Fuses 6.3 x 32

Fuses, Fast-blow, Glass



Excellent I²T characteristics

Welded element for enhanced vibration tolerance

Glass cartridge, nickel plated brass end caps

UL approved, E492698

SPECIFICATION:

Characteristic (time/current)	Fast-blow
Rated voltage	250 VAC
Construction form	Glass tube
Dimensions $\phi \times L$	6.3 x 32 mm

PRODUCT RANGE:

Art. Nr.	Rated current	Breaking capacity
RND 170-00096	0.5 A	35 A@ 250 VAC
RND 170-00098	0.63 A	35 A@ 250 VAC
RND 170-00101	0.75 A	35 A@ 250 VAC
RND 170-00103	0.8 A	35 A@ 250 VAC
RND 170-00080	1 A	35 A@ 250 VAC
RND 170-00081	1.25 A	100 A@ 250 VAC
RND 170-00082	1.5 A	100 A@ 250 VAC
RND 170-00083	1.6 A	100 A@ 250 VAC
RND 170-00088	2 A	100 A@ 250 VAC
RND 170-00089	2.5 A	100 A@ 250 VAC
RND 170-00092	3 A	100 A@ 250 VAC
RND 170-00093	3.15 A	100 A@ 250 VAC
RND 170-00094	4 A	200 A@ 250 VAC
RND 170-00095	5 A	200 A@ 250 VAC
RND 170-00097	6.3 A	200 A@ 250 VAC
RND 170-00099	7 A	200 A@ 250 VAC
RND 170-00100	7.5 A	200 A@ 250 VAC
RND 170-00102	8 A	200 A@ 250 VAC
RND 170-00084	10 A	200 A@ 250 VAC
RND 170-00085	12 A	200 A@ 250 VAC
RND 170-00086	12.5 A	200 A@ 250 VAC
RND 170-00087	15 A	200 A@ 250 VAC
RND 170-00090	20 A	200 A@ 250 VAC
RND 170-00091	25 A	200 A@ 250 VAC