

# Data Sheet

## FUJITSU Server PRIMERGY RX2540 M5 Rack Server

The data center standard without compromise

FUJITSU Server PRIMERGY will give you the servers you need to power any workload and changing business requirements. As business processes expand so does the need for applications. Each has its own resource footprint, so you need a way to optimize your computing to better serve your users. PRIMERGY systems will help you match your computing capabilities to your business priorities with our complete portfolio of expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers as well as hyper-converged multi-node servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, provide more agility in daily operations, and integrate seamlessly to let help you concentrate on core business functions.

FUJITSU Server PRIMERGY RX rack systems are versatile rack-optimized servers providing best-in-class performance and energy efficiency, and thus form the "standard" in each data center. PRIMERGY RX servers deliver more than 20 years of development and production know-how resulting in extremely low failure rates below market average, and lead to continuous operations and outstanding hardware availability.

### PRIMERGY RX2540 M5

The FUJITSU Server PRIMERGY RX2540 M5 sets higher standards for usability, scalability and cost efficiency. It is a 2U dual-socket rack server ideal for running enterprise applications, collaboration and messaging workloads as well as traditional databases. In addition, it substantially simplifies carrying out infrastructure-related tasks such as server virtualization and consolidation. As one of the key innovations, versatile performance is guaranteed by a new generation of processors.

The PRIMERGY RX2540 M5 can be equipped with two of the Intel® Xeon® Processor Scalable Family CPUs with up to 28 cores each. Along with new DDR4 memory technology with up to 3TB and optionally up to 12x Intel® Optane™ DC Persistent Memory NV-DIMM modules it boosts application performance so that it copes with the increasing data growth and to shorten time to business results. The modular design of the server offers excellent expandability with up to 28 disk drives, high storage density, up to 8 PCIe Gen 3 I/O expansion slots. A variety of onboard DynamicLoM options, plus its dual-port embedded LAN meet future requirements, cost-optimized. The PRIMERGY RX2540 M5 comes with two redundant hot-plug power supply units, offering up to 96% energy efficiency. The Cool-safe® Advanced Thermal Design allows operation in ambient temperatures of up to 45 °C/104 °F. Having both these features helps to reduce operational expenses.



# Features & Benefits

## Main Features

### Innovation meets Performance

- Wide choice of different types of Intel® Xeon® Scalable Processor Family. Each processor offers up to 28 cores, up to 56 threads, 12 memory channels enabling a significantly higher performance and efficiency. They rely on Intel® UltraPath Interconnect for an increased data rate between the CPUs. Intel® Optane™ DC persistent memory is an innovative memory technology that delivers a unique combination of affordable large capacity and persistence (non-volatility). It revolutionizes the data center memory-storage hierarchy of the past and brings massive data sets closer to the CPU for faster time to insight. In total, up to 7,680 GB main memory in a mixed mode (non-volatile memory + DDR4 @ 2,933 MT/s) are available. What's more is the support for up to 2x GPGPUs for fast processing.

### Enhanced Features for enhanced Computing

- The RX2540 M5 comes with onboard LAN for basic LAN, DynamicLoM via OCP slot for extended requirements. A mix&match storage drive bay configuration offers the choice of either up to 8x 3.5-inch HDD/SSD + 1x ODD, 12x 3.5-inch or up to 24x 2.5-inch, up to 8x PCIe 2.5-inch SSD + an additional rear option of 4x 2.5-inch drives, complemented by internal M.2 devices for hypervisor installations. Our power supply units with up to 96% energy efficiency and Fujitsu's Cool-safe® Advanced Thermal Design for higher ambient temperatures in the data center are available for this server.

### Foundation for Trust and Security

- Fujitsu ServerView Suite including tools for installation and deployment, permanent status monitoring and control, free-of-charge BIOS, firmware and selected software updates plus TPM2.0 modules and latest operating system support are a great addition.

### Revolutionize data center management

- Fujitsu ServerView Suite is a free-of-charge management software including tools for installation and deployment, permanent status monitoring and control as well as BIOS, firmware and selected software updates. In addition FUJITSU Software Infrastructure Manager (ISM) provides converged management across multiple data centers. The new ISM Essential license, available free-of-charge provides essential server management and converged monitoring functions.

## Benefits

- Ready for the future and data growth scenarios with the performance of two processors – marking the standard of tomorrow with an increase in computing power. Several innovations make this new CPU generation (code-named "Cascade Lake") even more powerful than the current-generation Intel® Xeon® Scalable processors, enabling robust compute capability and increased memory bandwidth for demanding workloads. Intel® Optane™ DC persistent memory technology will transform critical data workloads – from cloud and databases, to in-memory analytics, and content delivery networks but also for VDI, CAD or future technologies such as Artificial Intelligence of Virtual Reality applications.

- The right Ethernet connection for all: Basic via onboard LAN, extended with DynamicLoM via OCP guarantees the highest flexibility to integrate the server into existing infrastructures – now and in future without overhauling the existing infrastructure. Flexible expandability and diverse options for storage devices permits for the integration of existing and new SSD and HDD as needed. Less today, more in future – or vice versa. On top of that, this server is not only "greener", but also less expensive over time. Cool-safe® ATD and highly efficient hot-plug power supplies save energy costs.

- These features ensure lifecycle investment protection while the comprehensive tools of the Fujitsu ServerView Suite ease the administrators' life. Moreover, hardware and software security features are very important in a fast-paced world, especially considering cybercrime.

- Fujitsu offers comprehensive infrastructure management and server management solutions which is key to efficient data center operations. They provides all the functions for flexible and automated 24x7 IT operations and improves end-user productivity via intelligent and innovative system management solutions. ISM helps improve data center efficiency and overall IT Productivity with converged infrastructure management, paving the path to software-defined data center.

# Technical details

## PRIMERGY RX2540 M5

Base unit	PRIMERGY RX2540 M5 LFF	PRIMERGY RX2540 M5 LFF	PRIMERGY RX2540 M5 SFF	PRIMERGY RX2540 M5 SFF	PRIMERGY RX2540 M5 SFF
Housing types	Rack	Rack	Rack	Rack	Rack
Storage drive architecture	4x 3.5-inch SAS/SATA	max. 12x 3.5-inch SAS/SATA/PCIe	16x 2.5-inch SAS/SATA/PCIe	8x 2.5-inch SAS/SATA/PCIe	24x 2.5-inch SAS/SATA
Power supply	Hot-plug	Hot-plug	Hot-plug	Hot-plug	Hot-plug
Product Type	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server

## Mainboard

Mainboard type	D3384-B
Chipset	Intel® C624
Processor quantity and type	1 - 2 x Intel® Xeon® Processor Scalable Family

**Intel® Xeon® Bronze Processor** Intel® Xeon® Bronze 3204 (6C, 1.90 GHz, TLC: 8.25 MB, Turbo: 1.90 GHz, 9.6 GT/s, Mem bus: 2,133 MHz, 85 W, AVX Base 1.50 GHz, AVX Turbo 1.50 GHz)

**Intel® Xeon® Silver Processor** Intel® Xeon® Silver 4208 (8C, 2.10 GHz, TLC: 11 MB, Turbo: 2.50 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.60 GHz, AVX Turbo 2.00 GHz)

Intel® Xeon® Silver 4210 (10C, 2.20 GHz, TLC: 13.75 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.90 GHz, AVX Turbo 2.30 GHz)

Intel® Xeon® Silver 4214 (12C, 2.20 GHz, TLC: 16.5 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 2.40 GHz)

Intel® Xeon® Silver 4214Y (12C, 2.20 GHz, TLC: 16.5 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 1.80 GHz, AVX Turbo 2.40 GHz)

Intel® Xeon® Silver 4215 (8C, 2.50 GHz, TLC: 11 MB, Turbo: 3.00 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 85 W, AVX Base 2.00 GHz, AVX Turbo 2.60 GHz)

Intel® Xeon® Silver 4216 (16C, 2.10 GHz, TLC: 22 MB, Turbo: 2.70 GHz, 9.6 GT/s, Mem bus: 2,400 MHz, 100 W, AVX Base 1.40 GHz, AVX Turbo 2.30 GHz)

**Intel® Xeon® Gold Processor**

Intel® Xeon® Gold processor 5215 (10C, 2.50 GHz, up to 3.0 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 5215L (10C, 2.50 GHz, up to 3.0 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 5215M (10C, 2.50 GHz, up to 3.0 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 5217 (8C, 3.00 GHz, up to 3.4 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 5218 (16C, 2.30 GHz, up to 2.8 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 5218B (16C, 2.30 GHz, up to 2.8 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 5220 (18C, 2.20 GHz, up to 2.7 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 5220S (18C, 2.70 GHz, up to 2.7 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 5222 (4C, 3.80 GHz, up to 3.9 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6209U (20C, 2.10 GHz, up to 2.8 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6210U (20C, 2.50 GHz, up to 3.2 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6212U (24C, 2.40 GHz, up to 3.1 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6222V (20C, 1.80 GHz, up to 2.4 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6226 (12C, 2.70 GHz, up to 3.5 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6230 (20C, 2.10 GHz, up to 2.8 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6230T (20C, 2.10 GHz, up to 2.8 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6234 (8C, 3.30 GHz, up to 4.0 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6238 (22C, 2.10 GHz, up to 2.8 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6238L (22C, 2.10 GHz, up to 3.7 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6238M (22C, 2.10 GHz, up to 3.7 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6238T (22C/44T, 1.90 GHz, up to 2.7 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6240 (18C, 2.60 GHz, up to 3.3 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6240L (18C, 2.60 GHz, up to 3.3 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6240M (18C, 2.60 GHz, up to 3.3 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6240Y (18C, 2.60 GHz, up to 3.3 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6242 (16C, 2.80 GHz, up to 3.5 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6244 (8C, 3.60 GHz, up to 4.3 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6246 (12C, 3.30 GHz, up to 4.1 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6248 (20C, 2.50 GHz, up to 3.2 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6252 (24C, 2.10 GHz, up to 2.8 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6254 (18C, 3.10 GHz, up to 3.9 GHz, 10.4 GT/s)
Intel® Xeon® Gold processor 6262V (24C, 1.90 GHz, up to 2.5 GHz, 10.4 GT/s)

<b>Intel® Xeon® Platinum Processor</b>	Intel® Xeon® Platinum 8260 (24C, 2.40 GHz, TLC: 35.75 MB, Turbo: 3.10 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz)
	Intel® Xeon® Platinum 8260L (24C, 2.40 GHz, TLC: 35.75 MB, Turbo: 3.10 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz)
	Intel® Xeon® Platinum 8260M (24C, 2.40 GHz, TLC: 35.75 MB, Turbo: 3.10 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.90 GHz, AVX Turbo 2.60 GHz)
	Intel® Xeon® Platinum 8260Y (24C, 2.40 GHz, TLC: 35.75 MB, Turbo: 3.10 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.80 GHz, AVX Turbo 2.50 GHz)
	Intel® Xeon® Platinum 8268 (24C, 2.90 GHz, TLC: 35.75 MB, Turbo: 3.50 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 205 W, AVX Base 2.40 GHz, AVX Turbo 3.00 GHz)
	Intel® Xeon® Platinum 8270 (26C, 2.70 GHz, TLC: 35.75 MB, Turbo: 3.40 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 205 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)
	Intel® Xeon® Platinum 8276 (28C, 2.20 GHz, TLC: 38.5 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.60 GHz)
	Intel® Xeon® Platinum 8276L (28C, 2.20 GHz, TLC: 38.5 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.60 GHz)
	Intel® Xeon® Platinum 8276M (28C, 2.20 GHz, TLC: 38.5 MB, Turbo: 3.00 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 165 W, AVX Base 1.70 GHz, AVX Turbo 2.60 GHz)
	Intel® Xeon® Platinum 8280 (28C, 2.70 GHz, TLC: 38.5 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 205 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)
	Intel® Xeon® Platinum 8280L (28C, 2.70 GHz, TLC: 38.5 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 205 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)
	Intel® Xeon® Platinum 8280M (28C, 2.70 GHz, TLC: 38.5 MB, Turbo: 3.30 GHz, 10.4 GT/s, Mem bus: 2,933 MHz, 205 W, AVX Base 2.20 GHz, AVX Turbo 2.90 GHz)
<b>Memory slots</b>	24 (12 DIMMs per CPU, 6 channels with 2 slots per channel)
<b>Memory slot type</b>	DIMM (DDR4 / DDR-T for non-volatile memory modules)
<b>Memory capacity (min. - max.)</b>	8 GB - 7.5 TB
<b>Memory protection</b>	Advanced ECC Memory Scrubbing SDDC Rank sparing memory support Memory Mirroring support
<b>Memory notes</b>	Max. 6 slots populated with DCPMM modules per CPU, please see relevant system configurator for details. Memory Mirroring Mode with identical modules in both channel pairs of a bank (4 or 6 modules per bank) per CPU. Rank Sparing Mode with minimum of 2 modules single ranked (1R) or dual ranked (2R) or 1 module quad ranked (4R) per CPU.
<b>Standard memory modules</b>	8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx8 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx8 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4 32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4 64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4 128 GB (1 module(s) 128 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4 64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4
<b>Standard memory modules (for use in combination with non-volatile memory modules)</b>	96 GB (6 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4 64 GB (4 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4 128 GB (8 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 1Rx4 192 GB (6 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4 128 GB (4 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4 256 GB (8 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, DIMM, 2Rx4 768 GB (6 module(s) 128 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4 384 GB (6 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4 256 GB (4 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4 512 GB (8 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s, PC4-2933, LRDIMM, 4Rx4

<b>Non-volatile memory modules</b>	128 GB (1 module(s) 128 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 1Rx4				
	256 GB (2 module(s) 128 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 1Rx4				
	512 GB (2 module(s) 256 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 2Rx4				
	512 GB (4 module(s) 128 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 1Rx4				
	1024 GB (4 module(s) 256 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 2Rx4				
	2048 GB (4 module(s) 512 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 4Rx4				
	768 GB (6 module(s) 128 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 1Rx4				
	1536 GB (6 module(s) 256 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 2Rx4				
	3072 GB (6 module(s) 512 GB) DDR-T, registered, ECC, 2,666 MT/s, NVM, DCPMM, 4Rx4				
<b>Interfaces</b>					
<b>USB 3.0 ports</b>	5 x USB 3.0 (2x front, 2x rear, 1x internal) - for base units with max. drives count: 1x USB 2.0 front only				
<b>Graphics (15-pin)</b>	2 x VGA (thereof 1x front optional)				
<b>Serial 1 (9-pin)</b>	1 x serial RS-232-C optional, usable for iRMC or system or shared				
<b>Management LAN (RJ45)</b>	1 x dedicated management LAN port for iRMC S5 (10/100/1000 Mbit/s) Management LAN traffic can be switched to shared onboard LAN controller port, speed and connector is related to installed interface card.				
<b>Onboard or integrated Controller</b>					
<b>RAID controller</b>	All hardware storage controller options are described under Components For dedicated base units front AND rear storage drives may be connected to a single controller. Please see SystemArchitect for configuration options and restrictions.				
<b>SATA Controller</b>	Intel® C624, 1 x SATA channel for ODD				
<b>LAN Controller</b>	Intel® C624 2 x 1 Gbit/s onboard Optional DynamicLoM OCP adaptors: 4 x 1 Gbit/s Ethernet (RJ45) 2 x 10 Gbit/s Ethernet (RJ45) 2 x 10 Gbit/s SFP+ 4 x 10 Gbit/s SFP+ All supported features are described in relevant system configurator.				
<b>Remote management controller</b>	Integrated Remote Management Controller (iRMC S5, 512 MB attached memory incl. graphics controller) IPMI 2.0 compatible				
<b>GPU / coprocessor</b>	GFX/GPU support for dedicated base units. Please see relevant SystemArchitect for details and restrictions.				
<b>Onboard controller notes</b>	Onboard 8x S-ATA 6Gbit/s RAID Controller (RAID 0,1) for up to 8x S-ATA drives available.				
<b>Trusted Platform Module (TPM)</b>	Infineon / TPM 1.2 or TPM 2.0 module; TCG compliant (option)				
<b>Slots</b>					
<b>PCI-Express 3.0 x8</b>	3 x Low profile (2nd processor required for slot 4)				
<b>PCI-Express 3.0 x16</b>	3 x Low profile (2nd processor required for slot 5 and 6)				
<b>Slot Notes</b>	One PCIe Gen3 x8 slot may be occupied with a Modular RAID controller if configured. Important: 3 PCIe slots are supported with the first processor. 6 PCIe slots are supported with two processors. PCIe riser card options can expand number of slots by two (max. 8 in total) and support max. 4 full height slots. Possible slot length described in relevant system configurator.				
<b>Drive bays</b>					
<b>Storage drive bays</b>	3.5-inch or 2.5-inch hot-plug SAS/SATA				
<b>Accessible drive bays</b>	1 x 5.25/0.4-inch for CD-RW/DVD				
<b>Notes accessible drives</b>	All possible options described in relevant system configurator.				
<b>Optional hard disk bays</b>	4x 2.5-inch hot-plug SAS/SATA rear option				
<b>Drive bays (Base unit specific)</b>					
<b>Storage drive bays</b>	4 x 3.5-inch hot-plug SAS/SATA	12 x 3.5-inch hot-plug SAS/SATA	16 x 2.5-inch hot-plug SAS/SATA	8 x 2.5-inch hot-plug SAS/SATA	24 x 2.5-inch hot-plug SAS/SATA
<b>Accessible drive bays</b>	1 x 5.25/0.4-inch for CD-RW/DVD		1 x 5.25/0.4-inch for CD-RW/DVD	1 x 5.25/0.4-inch for CD-RW/DVD	
<b>Optional accessible drives</b>	ODD 5.25" possible	ODD 5.25" NOT possible	ODD 5.25" possible	ODD 5.25" possible	ODD 5.25" NOT possible

**General system information**

Number of fans	6
Fan configuration	redundant / hot-plug
Fan notes	3x2 redundant

**Operating panel**

Operating buttons	On/off switch Reset button NMI button ID button
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)

**BIOS**

BIOS features	UEFI compliant Legacy BIOS compatibility customer configuration option Secure boot support ROM based setup utility GPT support for boot drives larger than 2.2 TB Memory Redundancy support (Mirroring, Sparing) IPMI support Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Linux versions Local and remote update via ServerView Update Manager IPv4/IPv6 remote PXE & iSCSI boot support Cryptographically Signed BIOS Firmware Update HTTP and HTTPS Boot PCIe Bifurcation configurable
---------------	---

**Operating Systems and Virtualization Software**

Certified or supported operating systems and virtualization software	Windows Server 2019 Datacenter
	Windows Server 2019 Standard
	Windows Server 2019 Essentials
	Windows Server Datacenter, version 1809
	Windows Server Standard, version 1809
	Hyper-V Server 2016
	Windows Server 2016 Datacenter
	Windows Server 2016 Standard
	Windows Server 2016 Essentials
	Windows Storage Server 2016 Standard
	Windows Server Datacenter, version 1709
	VMware vSphere™ 6.7
	VMware vSphere™ 6.5
	SUSE® Linux Enterprise Server 12
	Red Hat® Enterprise Linux 8
	Red Hat® Enterprise Linux 7
Oracle® Linux 7	
Oracle® VM 3	
Univention Corporate Server 4	

Operating system release link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473</a>
-------------------------------	---

---

**Operating Systems and Virtualization Software**


---

**Operating system notes** Support of other Linux derivatives on demand

---

**Server Management and Infrastructure Management**


---

<b>Standard</b>	<ul style="list-style-type: none"> <li>Infrastructure Manager (ISM) Essential <ul style="list-style-type: none"> <li>Node Management</li> <li>Health status Monitoring and Control</li> <li>Capacity/Threshold Management</li> <li>Power Management</li> <li>Converged Management</li> <li>Auto Discovery</li> <li>Remote Management</li> <li>Update Management</li> <li>Logging and Auditing</li> </ul> </li> <li>ServerView Suite (Deploy) <ul style="list-style-type: none"> <li>ServerView Installation Manager</li> <li>ServerView Scripting Toolkit</li> </ul> </li> <li>ServerView Suite (Control) <ul style="list-style-type: none"> <li>ServerView Operations Manager (incl. PDA and ASR &amp; R)</li> <li>ServerView Agents and CIM provider</li> <li>ServerView Agentless Management</li> <li>ServerView System Monitor</li> <li>SVOM- Event Manager</li> <li>ServerView RAID Manager</li> <li>SVOM- Threshold Manager</li> <li>Power Monitor (monitoring the Power Consumption)</li> <li>Power Management (iRMC)</li> <li>Storage Management (server) with SVOM/SV-RAID</li> </ul> </li> <li>ServerView Suite (Maintain) <ul style="list-style-type: none"> <li>iRMC S5 (Remote Management)</li> <li>System Update Manager (BIOS, Firmware, Windows Drives and SV Agents)</li> <li>Performance management (SVOM)</li> <li>Asset Management</li> <li>Primecollect</li> <li>Customer Self Service</li> <li>Online Diagnostics</li> </ul> </li> <li>ServerView Suite (Integrate) <ul style="list-style-type: none"> <li>ServerView Integration packs for MS System Center, VMware vCenter, VMware vRealize, Nagios, and HP SIM</li> </ul> </li> </ul>
<b>Option</b>	<ul style="list-style-type: none"> <li>ServerView Suite (Maintain) <ul style="list-style-type: none"> <li>ServerView eLCM</li> <li>iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media</li> </ul> </li> <li>ServerView Suite (Dynamize) <ul style="list-style-type: none"> <li>ServerView Virtual IO Manager (SVIOM)</li> </ul> </li> <li>Infrastructure Manager (ISM) <ul style="list-style-type: none"> <li>Automate device configuration</li> <li>Mass OS installation</li> <li>Node Management</li> <li>Health status Monitoring and Control</li> <li>Capacity/Threshold Management</li> <li>Power Management</li> <li>Converged Management</li> <li>Auto Discovery</li> <li>Virtual-IO Management</li> <li>Network topology Management</li> <li>Remote Management</li> <li>Update Management</li> <li>Logging and Auditing</li> <li>Integrate in to <ul style="list-style-type: none"> <li>Enterprise Management</li> <li>Vendor specific Management</li> <li>Monitor 3rd party platforms</li> </ul> </li> </ul> </li> </ul>
<b>Server Management notes</b>	Regarding dependencies for ServerView Suite software products see dedicated product data sheets.



<b>Dimensions / Weight</b>	
Rack (W x D x H)	482.4 mm (Bezel) / 445 mm (Body) x 770 x 86.6 mm
Mounting Depth Rack	740 mm
Height Unit Rack	2 U
19" rackmount	Yes
Mounting Cable depth rack	200 mm (1,000 mm Rack recommended)
Weight	up to 25 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option
<b>Environment</b>	
Operating ambient temperature	5 - 45 °C (41 - 113 °F)
Operating temperature note	Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. For detailed information see relevant system configurator. Ambient temperature limitation may differ for liquid cooled models. Please refer to the SystemArchitect for detailed information.
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe">http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe</a>
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	Typical noise : 43 dB(A) (idle) / 43 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	Typical noise : 6.1 B (idle) / 6.0 B (operating)
Noise notes	Noise emissions depends on operation modes, system configuration and ambient temperature. Typical hardware configuration which is the base for measurement according to ISO 7779: 2x PSU 450W. 2x CPU Xeon 85W, 4x RAM 16GB, 2x HDD 500GB SATA, 6x LAN 1 Gbit/s
<b>Electrical values</b>	
Power supply configuration	1 x hot-plug power supply or 2x hot-plug power supply for redundancy
Hot-plug power supply redundancy	Optional
Active power (max. configuration)	715 W
Apparent power (max. configuration)	753 VA
Heat emission (max. configuration)	2574.0 kJ/h (2439.7 BTU/h)
Rated current max.	7.68 A (100 V) / 2.98 A (240 V)
Active power note	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: <a href="http://configurator.ts.fujitsu.com/public/">http://configurator.ts.fujitsu.com/public/</a>
Power supply	450W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 800W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 800W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz 1200W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz; 110V range: 1000W, less than 110V: 900W 800W hot-plug, 92% (equivalent to Gold efficiency) –48V DC 1300W hot plug, 94% (equivalent to Platinum efficiency) 380V DC
Power supply notes	Power Safeguard adapts system performance in case the power requirements exceeds supply limits. !96% Titanium Power supply unit is only released for 200-240V
<b>Compliance</b>	
Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment)
Germany	GS
Europe	CE
USA/Canada	CSAc/us FCC Class A ICES-003 / NMB-003 Class A
Japan	VCCI:V3 Class A + JIS 61000-3-2
Russia	EAC
South Korea	KC
China	CCC

<b>Compliance</b>	
Australia/New Zealand	RCM
Taiwan	BSMI
India	BIS R41004006
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>
Compliance notes	<p>There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.</p> <p>* Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.</p>

## Components

<b>Backup Drives</b>	LTO6HH Ultrium, 2,500 GB, 160 MB/s, half height, SAS 6Gb/s
	LTO7HH Ultrium, 2,500 GB, 300 MB/s, half height, SAS 6Gb/s
	RDX Drive, 320 GB, 500 GB, 1 TB, 25 MB/s, half height, USB 3.0
<b>Optical drives</b>	Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I
	DVD Super Multi ultra slim, (8x DVD; 24x CD), ultraslim, SATA I
<b>Hard disk drives</b>	HDD SATA, 6 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical	

## Hard disk drives

HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 10 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 4 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical

**Solid-State-Drive**

SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.6 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.5 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1.0 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
SSD M.2 SATA, 6 Gb/s, 480 GB, non hot plug, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
SSD M.2 SATA, 6 Gb/s, 240 GB, non hot plug, enterprise, for VMware
SSD M.2 SATA, 6 Gb/s, 240 GB, non hot plug, enterprise, 1.4 DWPD (Drive Writes Per Day for 5 years)
SSD M.2 SATA, 6 Gb/s, 150 GB, non hot plug, enterprise, 1.5 DWPD (Drive Writes Per Day for 5 years)
SSD M.2 SATA, 6 Gb/s, 150 GB, non hot plug, enterprise

**Solid-State-Drive**

SSD SAS, 12 Gb/s, 960 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 3.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years), SED
SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 800 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 800 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 480 GB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 3.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years), SED
SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 400 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 400 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 0.9 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 3.2 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 2.3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 2.3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 3.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 3.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years), SED
SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.6 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
SSD SAS, 12 Gb/s, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)

**PCIe SSD & SATA DOM SSD**

PCIe-SSD SFF, 750 GB, Write-Intensive, hot-plug, 2.5-inch, Flash drive, 30 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.2 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 4 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 4 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 0.6 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.1 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 2 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 2 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 0.6 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 1 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD SFF, 1 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD AIC, 750 GB, Write-Intensive, HHHL, Flash drive, 30 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD AIC, 375 GB, Write-Intensive, HHHL, Flash drive, 30 DWPD (Drive Writes Per Day for 5 years)
PCIe-SSD AIC, 4 TB, Mixed-use, HHHL, Flash drive, 3.1 DWPD (Drive Writes Per Day for 5 years)
Dual microSD 64GB Enterprise

**SCSI / SAS Controller**

LSI PSAS CP400e LP SAS Ctrl. 12 Gbit/s 8 ports ext. PCIe 3.0 x8
Fujitsu PSAS CP403i SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
Fujitsu PSAS CP400i SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
Fujitsu PSAS CP400e FH SAS Ctrl. 12 Gbit/s 8 ports ext. PCIe 3.0 x8

<b>RAID Controller</b>	Fujitsu PRAID EP580i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP540e LP, RAID 5/6 Ctrl., SAS 12 Gbit/s, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP540e FH, RAID 5/6 Ctrl., SAS 12 Gbit/s, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP520i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP420i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108
	Fujitsu PRAID EP420i for SafeStore, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108
	Fujitsu PRAID EP400i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU based on LSI SAS3108
	Fujitsu PRAID CP400i, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 1E, 10, 5, 50, No FBU support
<b>Fibre Channel controller</b>	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Cavium QLE2740 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Cavium QLE2742 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Emulex LPe32000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPe32002-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe31000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style
<b>Communication, Network</b>	Converged Network Adapter 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 ( Cavium )
	Ethernet Ctrl. 1 x 100 Gbit/s PCIe 3.0 x16 QSFP28 ( Cavium )
	Ethernet Ctrl. 1 x 100 Gbit/s PCIe 3.0 x16 QSFP28 ( Mellanox )
	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 ( Cavium )
	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 ( Intel® )
	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 SFP+ ( Cavium )
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 ( Cavium )
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 ( Intel® )
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 ( Mellanox )
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Intel® )
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )
	Ethernet Ctrl. 2 x 40 Gbit/s PCIe 3.0 x16 QSFP ( Mellanox )
	Ethernet Ctrl. 4 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 ( Cavium )
	Ethernet Ctrl. 4 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 ( Intel® )
	Ethernet Ctrl. 4 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 SFP+ ( Cavium )
	Ethernet Ctrl. 4 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Intel® )
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )
	InfiniBand HCA 1 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed ( Mellanox )
	InfiniBand HCA 2 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed ( Mellanox )
	Interface modul for Dynamic LoM 2 x 10 Gbit/s RJ45 ( Intel® )
	Interface modul for Dynamic LoM 2 x 10 Gbit/s SFP+ ( Intel® )
	Interface modul for Dynamic LoM 4 x 10 Gbit/s SFP+ ( Intel® )
	Interface modul for Dynamic LoM 4 x 1 Gbit/s RJ45 ( Intel® )
	MPO x 40 Gbit/s ( )
	Omni Path 1 x PCIe 3.0 x16 ( Intel® )

<b>Graphics add on cards</b>	PCIe 3.0 x16
<b>Graphics</b>	NVIDIA® Quadro® P400 , 2 GB, PCIe x16, 3 x miniDP
<b>Rack infrastructure</b>	Rackmount kit full extraction (820mm), tool less mounting, length variable 559-914mm Rack Mount Kit Cable Management for 19-inch DataCenter / PRIMECENTER Racks Cable Arm 2U for PRIMECENTER- and 3rd-party racks
<b>Warranty</b>	
<b>Warranty period</b>	3 years
<b>Warranty type</b>	Onsite warranty
<b>Warranty Terms &amp; Conditions</b>	<a href="http://www.fujitsu.com/support">www.fujitsu.com/support</a>
<b>Product Support Services - the perfect extension</b>	
<b>Support Pack Options</b>	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)
<b>Recommended Service</b>	24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
<b>Service Lifecycle</b>	5 years after end of product life
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a>

# More information

## Fujitsu products, solutions & services

In addition to FUJITSU Server PRIMERGY RX2540 M5, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about FUJITSU Server PRIMERGY RX2540 M5, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/primergy](http://www.fujitsu.com/primergy)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>  
Copyright 2019 FUJITSU LIMITED

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

**Contact**  
FUJITSU LIMITED

Website: [www.fujitsu.com](http://www.fujitsu.com)  
2019-11-01 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>  
Copyright 2019 FUJITSU LIMITED