HD34-24-16SN-072 ✓ ACTIVE

DEUTSCH | DEUTSCH HD, DEUTSCH HD30

TE Internal #: HD34-24-16SN-072

Housing for Female Terminals, Wire-to-Wire, 16 Position, Sealable, Wire & Cable, Power & Signal, Panel Mount, -55 - 125 °C [-67 - 257

°F], Hybrid

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > DEUTSCH HD30 HOUSINGS











Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 2.39 mm [.094 in]

Connector System: Wire-to-Wire

Number of Positions: 16

Sealable: Yes

All DEUTSCH HD30 HOUSINGS (357)

Features

Product Type Features

Connector Shape	Circular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Contact Retainer
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Blank Cavity Position	0
Connector Modification	Adapter
Connector Seal Code	N Seal
Number of Positions	16



Electrical Characteristics

Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V

Body Features

Cable Exit Angle	180°
Body Material	Aluminum

Contact Features

Contact Size	Size 12
Contact Type	Socket
Mating Pin Diameter	2.39 mm[.094 in]
Contact Current Rating (Max)	25 A

Mechanical Attachment

Mounting Feature	With
Terminal Position Assurance	No
Strain Relief	Add By Accessory
Mating Alignment Type	Guide Post
Mating Alignment	With
Connector Mounting Type	Panel Mount

Dimensions

Product Width	50.8 mm[2 in]
Product Length	68.5 mm[2.697 in]
Product Height	47.53 mm[1.875 in]
Accepts Wire Insulation Diameter Range	3.4 – 4.32 mm[.134 – .17 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Power & Signal
Industry Standards	

industry Standards

Degree of Protection	IP67	

Packaging Features

r delicaging Cadmitty	Packaging Quantity	80	
-----------------------	--------------------	----	--



Packaging Method	Вох	
Other		
Serviceable	Yes	
Connector Position Assurance Capable	No	

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













TE Part # 0413-214-1205 SEALING PLUG, SIZE 12, KEYING, YEL




TE Part # CAT-D48-ST273 DEUTSCH SOLID CONTACTS



TE Part # CAT-D48-SFT273 DEUTSCH STAMPED & FORMED CONTACTS



TE Part # HD30-24BT-BK BOOT, 24SZ, ST, BLK



TE Part # 16-04477 GASKET, 24SZ, BLK, HD30



TE Part # HD30-24BT BOOT, 24SZ, ST, GRY



TE Part # HD30-24BT-90-BK BOOT, 24SZ, RA, BLK



Also in the Series | DEUTSCH HD



Automotive Connector Caps & Covers Automotive Housings(742)







Insertion & Extraction Tools(11)



Other Automotive Connector Accessories(11)



PCB Headers & Receptacles(1)

Also in the Series | DEUTSCH HD30

Housing for Female Terminals, Wire-to-Wire, 16 Position, Sealable, Wire & Cable, Power & Signal, Panel Mount, -55 – 125 °C [-67 – 257 °F], Hybrid





Automotive Connector Caps & Covers (18)




Automotive Housings(359)



Automotive Seals & Cavity Plugs(11)





Customers Also Bought





Documents

Product Drawings

REC, 16P, AL, N, THD ADPT, DRAIN, 12, S

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_HD34-24-16SN-072_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_HD34-24-16SN-072_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_HD34-24-16SN-072_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Housing for Female Terminals, Wire-to-Wire, 16 Position, Sealable, Wire & Cable, Power & Signal, Panel Mount, -55 – 125 °C [-67 – 257 °F], Hybrid



Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English