

HP USB-C™ Adapters



HP USB-C™ to RJ45 Adapter

Expand your connectivity

Use the adapter to convert your USB-C™ port to a wired Ethernet connection and reliably access to secure corporate networks or other Internet connections.

Simple to use

Easily connect to your network through your device¹ USB-C™ port with the HP USB-C™ to RJ45 Adapter.

World-class support

Rest easy with a one-year parts replacement limited warranty.

HP USB-C™ to USB 3.0 Adapter

Enable easy device connectivity

Convert your notebook or tablet's USB-C™ port to USB 3.0 with the HP USB-C™ to USB 3.0 Adapter.

Simple to use

Use the adapter to connect to your frequently-used USB 3.0 devices through your notebook or tablet's USB-C™ port.

World-class support

Rest easy with a one-year parts replacement limited warranty. Get the reassurance of a one-year limited warranty.



¹See product QuickSpecs for exact compatibility.

HP USB-C™ to RJ45/USB3/USB-C™ Adapter

Be more productive

Easily enable reliable connectivity through wired USB 3.0, Ethernet, and USB-C™ power-in connections with the HP USB-C™ to RJ45/USB3/USB-C™ Adapter.

Get online

Use the adapter to convert your USB-C™ port to a wired Ethernet connection and reliably access secure corporate networks or other Internet connections where wireless is spotty or unavailable (Ethernet cable required).

Charge it up

Connect to your wired USB 3.0 peripherals and power your device with the convenient USB-C™ power in connector at the same time.

World-class support

Rest easy with a one-year parts replacement limited warranty.



HP USB-C™ to 3 mm and 4.5 mm Adapter

Power up with added simplicity

Travel light with the HP USB-C™ to 3 mm and 4.5 mm Adapter, which lets you use one power adapter to charge your tablet and notebook.¹

Easy to use

Connect one end of the adapter to the USB-C™ port on your tablet or notebook¹, and on the other end, connect your HP AC Adapter up to 65W.

World-class support

Rest easy with a one-year parts replacement limited warranty.



¹See product QuickSpecs for exact compatibility.

HP USB-C™ to USB-A Hub



USB expansion for wherever you work

Optimize your workspace with easy connectivity to your frequently-used accessories in the office and on the road. Convert your notebook or tablet's USB-C™ port to a portable, lightweight USB hub and enable simultaneous connections to up to three USB accessories with the HP USB-C to USB-A Hub.

No software required

Simply plug the attached USB-C™ cable into any available USB-C™ port on your device, and the hub is ready for your USB accessories.

Keep the accessories you trust

Charge your cell phone with the hub's USB 3.0 charging port and use the other two USB ports to connect to your external storage, keyboard, mouse, headset, optical drive, and more.

Rest easy

Get the reassurance of a one-year limited warranty.

Specifications



	HP USB-C™ to RJ45/USB3/USB-C™ Adapter	HP USB-C™ to USB 3.0 Adapter	HP USB-C™ to 3 mm and 4.5 mm Adapter
Part number	N2Z64AA	N2Z63AA	N2Z65AA
Dimensions	7.12 x 2.80 x 0.74 in (18.07 x 7.10 x 1.87 cm)	5.55 x 0.92 x 0.43 in (14.08 X 2.33 X 1.10 cm)	6.32 x 1.87 x .75 in (16.06 x 4.75 x 1.90 cm)
Weight	8.64 ounces (245 g)	.71 ounces (20 g)	1.76 ounces (50 g)
Connectors	USB-C™ to RJ45/USB 3/USB-C	USB-C™ to USB 3.0 Adapter	3mm DC jack, 4.5mm DC jack, and USB-C™
LEDs	Network connection indicators	None	None
Environmental Design	Operating Temperature: 0°C to 40°C Non-operating (storage): -20°C to 60°C Humidity: 20%-80% RH Storage Humidity: 20%-90%RH EMI and Safety Certifications: CE/FCC&IC/BSMI/VCCI/C-tick(RCM)/ UL&cUL/KCC/EAC/UK/SABS&NRCS/ CB	Operating Temperature: 0°C to 40°C Non-operating (storage): -20°C to 60°C Humidity: 20%-80% RH Storage Humidity: 20%-90%RH EMI and Safety Certifications: CE/FCC&IC/BSMI/VCCI/C-tick(RCM)/ UL&cUL	Operating Temperature: 0°C to 40°C Non-operating (storage): -40 to +70 °C Humidity: 50% RH



	HP USB-C™ to RJ45 Adapter	HP USB-C™ to USB-A Hub
Part number	V7W66AA	Z6A00AA
Dimensions	7.1 x 0.8 x 0.7 in (18.0 X 2.1 x 1.7 cm)	2.63 x 1.63 x 0.42 in (6.68 x 4.14 x 1.05 cm)
Weight	2.5 ounces (71.4 g)	1.28 ounces (36.5 g)
Connectors	1 x 22 pin USB Type C™	HP USB-C™ to USB-A Hub
LEDs	Yes	None
Environmental Design	Operating Temperature: 0C to 70C Non-operating (storage): -55C to +125C Humidity: Level 3 Storage Humidity: <=90% RH in Al bag EMI and Safety Certifications: EMC, CB, VCCI, CE, REACH, FCC, RCM, KCC, EAC, Ukraine	Operating Temperature: 0C to 35C Non-operating (storage): -10C to +35C Humidity: 5%-85%RH Storage Humidity: 85%RH EMI and Safety Certifications: CE/CB/FCC&IC/BSMI/VCCI/RCM/KCC/ EAC/UL&Cul/Ukraine

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.

4AA6-1058ENW, January 2017, Rev 3.

