

Coaxial Cable Connector 16_MM CX-50-1-1/111_O

Description

Right angle cable plug

Interface standards
SUHNER-MM CX



Technical Data

Electrical Data

| | |
|--------------------------|-------|
| Impedance | 50 Ω |
| Interface frequency max. | 6 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | soldered |
| Outer contact | crimped |
| Weight | 0.0007 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -55 °C to 155 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------|--|
| Centre contact | Bronze | Gold Plating (Nickel underplated) |
| Outer contact | Brass | Gold Plating (without Nickel underplating) |
| Body | Brass | Gold Plating (without Nickel underplating) |
| Insulator | PFA / PTFE | |
| Crimp ferrule | Brass | Gold Plating (without Nickel underplating) |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00006008 |
| Catalogue drawing | DOU-00006007 |
| Assembly instruction | DOC-0000779355 |

Ordering Information

| | |
|----------------------|------------------------|
| Single package | 16_MM CX-50-1-1/111_OE |
| Bulk 100 pcs package | 16_MM CX-50-1-1/111_OH |

Additional Information

| | |
|-----------------|------------------------|
| Suitable cables | RG_178_B/U, RG_196_A/U |
|-----------------|------------------------|