




THT LABELS: PERMASLEEVE® WIRE MARKING SLEEVES

THT WIRE & CABLE MATERIALS:

B-7641 PERMASLEEVE® LSZH LOW SMOKE ZERO HALOGEN SLEEVES - SINGLE-SIDED PRINTABLE

2:1 shrink ratio. Designed for wire identification and insulation purposes. These sleeves are suitable for use in applications that require low smoke halogen free, self-extinguishing markers.



Part No.	Reference	Pieces Per Roll	Sleeves Per Roll	Range of Wire Dia. Min - Max (mm)	Approx. Wire Gauge	Sleeve Width (A mm)	Sleeve Height (B mm)	Verticle Repeat (C mm)	Supplied Dia. (mm)	Recovered Dia. (mm)	Recovered Wall Thickness (mm)	Rec. Printer	Rec. Ribbon Series
141201	LSZH-125-150-YL-2	5000	2500	1.58 - 2.79	20 to 16	19.05	6.20	12.70	3.20	1.60	0.6 - 0.07	PR Plus	R-6000/R-6600
141202	LSZH-094-2-WT	2500	2500	1.19 - 2.03	24 to 20	50.01	5.00	12.70	2.40	1.20	0.5 - 0.1	PR Plus	R-6000/R-6600
141203	LSZH-094-2-WT-2	5000	2500	1.19 - 2.03	24 to 20	24.99	5.00	12.70	2.40	1.20	0.5 - 0.1	PR Plus	R-6000/R-6600
141206	LSZH-094-2-WT-S	500	500	1.19 - 2.03	24 to 20	50.01	5.00	12.70	2.40	1.20	0.5 - 0.1	PR Plus	R-6000/R-6600
141207	LSZH-094-2-YL	2500	2500	1.19 - 2.03	24 to 20	50.01	5.00	12.70	2.40	1.20	0.5 - 0.1	PR Plus	R-6000/R-6600
141208	LSZH-094-2-YL-2	5000	2500	1.19 - 2.03	24 to 20	24.99	5.00	12.70	2.40	1.20	0.5 - 0.1	PR Plus	R-6000/R-6600
141211	LSZH-094-2-YL-S	500	500	1.19 - 2.03	24 to 20	50.01	5.00	12.70	2.40	1.20	0.5 - 0.1	PR Plus	R-6000/R-6600
141212	LSZH-125-2-WT	2500	2500	1.58 - 2.79	20 to 16	50.01	6.20	12.70	3.20	1.60	0.6-0.07	PR Plus	R-6000/R-6600
141213	LSZH-125-2-WT-2	5000	2500	1.58 - 2.79	20 to 16	24.99	6.20	12.70	3.20	1.60	0.6-0.07	PR Plus	R-6000/R-6600
141216	LSZH-125-2-WT-S	500	500	1.58 - 2.79	20 to 16	50.01	6.20	12.70	3.20	1.60	0.6-0.07	PR Plus	R-6000/R-6600
141217	LSZH-125-2-YL	2500	2500	1.58 - 2.79	20 to 16	50.01	6.20	12.70	3.20	1.60	0.6-0.07	PR Plus	R-6000/R-6600
141218	LSZH-125-2-YL-2	5000	2500	1.58 - 2.79	20 to 16	24.99	6.20	12.70	3.20	1.60	0.6-0.07	PR Plus	R-6000/R-6600
141221	LSZH-125-2-YL-S	500	500	1.58 - 2.79	20 to 16	50.01	6.20	12.70	3.20	1.60	0.6-0.07	PR Plus	R-6000/R-6600
141222	LSZH-187-2-WT	2500	2500	2.39 - 3.84	16 to 10	50.01	8.40	15.88	4.80	2.40	0.6 - 0.07	PR Plus	R-6000/R-6600
141223	LSZH-187-2-WT-2	5000	2500	2.39 - 3.84	16 to 10	24.99	8.40	15.88	4.80	2.40	0.6 - 0.07	PR Plus	R-6000/R-6600
141226	LSZH-187-2-WT-S	500	500	2.39 - 3.84	16 to 10	50.01	8.40	15.88	4.80	2.40	0.6 - 0.07	PR Plus	R-6000/R-6600
141227	LSZH-187-2-YL	2500	2500	2.39 - 3.84	16 to 10	50.01	8.40	15.88	4.80	2.40	0.6 - 0.07	PR Plus	R-6000/R-6600
141228	LSZH-187-2-YL-2	5000	2500	2.39 - 3.84	16 to 10	24.99	8.40	15.88	4.80	2.40	0.6 - 0.07	PR Plus	R-6000/R-6600
141231	LSZH-187-2-YL-S	500	500	2.39 - 3.84	16 to 10	50.01	8.40	15.88	4.80	2.40	0.6 - 0.07	PR Plus	R-6000/R-6600
141232	LSZH-250-2-WT	2500	2500	3.18 - 5.46	12 to 8	50.01	11.30	19.05	6.40	3.20	0.7 - 0.07	PR Plus	R-6000/R-6600
141233	LSZH-250-2-WT-2	5000	2500	3.18 - 5.46	12 to 8	24.99	11.30	19.05	6.40	3.20	0.7 - 0.07	PR Plus	R-6000/R-6600
141236	LSZH-250-2-WT-S	500	500	3.18 - 5.46	12 to 8	50.01	11.30	19.05	6.40	3.20	0.7 - 0.07	PR Plus	R-6000/R-6600
141237	LSZH-250-2-YL	2500	2500	3.18 - 5.46	12 to 8	50.01	11.30	19.05	6.40	3.20	0.7 - 0.07	PR Plus	R-6000/R-6600
141238	LSZH-250-2-YL-2	5000	2500	3.18 - 5.46	12 to 8	24.99	11.30	19.05	6.40	3.20	0.7 - 0.07	PR Plus	R-6000/R-6600
141241	LSZH-250-2-YL-S	500	500	3.18 - 5.46	12 to 8	50.01	11.30	19.05	6.40	3.20	0.7 - 0.07	PR Plus	R-6000/R-6600
141242	LSZH-375-2-WT	1000	1000	3.18 - 5.46	8 to 4	50.01	15.80	25.40	9.50	4.80	0.7 - 0.05	PR Plus	R-6000/R-6600
141243	LSZH-375-2-WT-2	2000	1000	3.18 - 5.46	8 to 4	24.99	15.80	25.40	9.50	4.80	0.7 - 0.05	PR Plus	R-6000/R-6600
141246	LSZH-375-2-WT-S	250	250	3.18 - 5.46	8 to 4	50.01	15.80	25.40	9.50	4.80	0.7 - 0.05	PR Plus	R-6000/R-6600
141247	LSZH-375-2-YL	1000	1000	3.18 - 5.46	8 to 4	50.01	15.80	25.40	9.50	4.80	0.7 - 0.05	PR Plus	R-6000/R-6600
141248	LSZH-375-2-YL-2	2000	1000	3.18 - 5.46	8 to 4	24.99	15.80	25.40	9.50	4.80	0.7 - 0.05	PR Plus	R-6000/R-6600
141251	LSZH-375-2-YL-S	250	250	3.18 - 5.46	8 to 4	50.01	15.80	25.40	9.50	4.80	0.7 - 0.05	PR Plus	R-6000/R-6600
141252	LSZH-500-2-WT	500	500	6.35 - 11.43	6 to 1	50.01	12.10	31.75	12.70	6.40	0.7 - 0.05	PR Plus	R-6000/R-6600
141253	LSZH-500-2-WT-2	1000	500	6.35 - 11.43	6 to 1	24.99	12.10	31.75	12.70	6.40	0.7 - 0.05	PR Plus	R-6000/R-6600
141256	LSZH-500-2-WT-S	250	250	6.35 - 11.43	6 to 1	50.01	12.10	31.75	12.70	6.40	0.7 - 0.05	PR Plus	R-6000/R-6600
141257	LSZH-500-2-YL	500	500	6.35 - 11.43	6 to 1	50.01	12.10	31.75	12.70	6.40	0.7 - 0.05	PR Plus	R-6000/R-6600
141258	LSZH-500-2-YL-2	1000	500	6.35 - 11.43	6 to 1	24.99	12.10	31.75	12.70	6.40	0.7 - 0.05	PR Plus	R-6000/R-6600
141261	LSZH-500-2-YL-S	250	250	6.35 - 11.43	6 to 1	50.01	12.10	31.75	12.70	6.40	0.7 - 0.05	PR Plus	R-6000/R-6600
141262	LSZH-750-2-WT	250	250	9.53 - 17.78	2 to 4/0	50.01	31.40	41.30	19.00	9.50	0.8 - 0.07	PR Plus	R-6000/R-6600
141263	LSZH-750-2-WT-2	500	250	9.53 - 17.78	2 to 4/0	24.99	31.40	41.30	19.00	9.50	0.8 - 0.07	PR Plus	R-6000/R-6600
141266	LSZH-750-2-WT-S	100	100	9.53 - 17.78	2 to 4/0	50.01	31.40	41.30	19.00	9.50	0.8 - 0.07	PR Plus	R-6000/R-6600
141267	LSZH-750-2-YL	250	250	9.53 - 17.78	2 to 4/0	50.01	31.40	41.30	19.00	9.50	0.8 - 0.07	PR Plus	R-6000/R-6600
141268	LSZH-750-2-YL-2	500	250	9.53 - 17.78	2 to 4/0	24.99	31.40	41.30	19.00	9.50	0.8 - 0.07	PR Plus	R-6000/R-6600
141271	LSZH-750-2-YL-S	100	100	9.53 - 17.78	2 to 4/0	50.01	31.40	41.30	19.00	9.50	0.8 - 0.07	PR Plus	R-6000/R-6600
141272	LSZH-1000-2-WT	250	250	11.43 - 24.13	2/0 to 0.95 DIA	50.01	41.50	50.80	25.40	12.70	0.9 - 0.07	PR Plus	R-6000/R-6600
141273	LSZH-1000-2-WT-2	500	250	11.43 - 24.13	2/0 to 0.95 DIA	24.99	41.50	50.80	25.40	12.70	0.9 - 0.07	PR Plus	R-6000/R-6600
141276	LSZH-1000-2-WT-S	100	100	11.43 - 24.13	2/0 to 0.95 DIA	50.01	41.50	50.80	25.40	12.70	0.9 - 0.07	PR Plus	R-6000/R-6600
141277	LSZH-1000-2-YL	250	250	11.43 - 24.13	2/0 to 0.95 DIA	50.01	41.50	50.80	25.40	12.70	0.9 - 0.07	PR Plus	R-6000/R-6600
141278	LSZH-1000-2-YL-2	500	250	11.43 - 24.13	2/0 to 0.95 DIA	24.99	41.50	50.80	25.40	12.70	0.9 - 0.07	PR Plus	R-6000/R-6600
141281	LSZH-1000-2-YL-S	100	100	11.43 - 24.13	2/0 to 0.95 DIA	50.01	41.50	50.80	25.40	12.70	0.9 - 0.07	PR Plus	R-6000/R-6600
141282	LSZH-1500-2-WT	250	250	19.05 - 35.56	n/a	50.01	38.10	76.20	38.10	19.10	1.0 - 0.07	PR Plus	R-6000/R-6600
141283	LSZH-1500-2-YL	250	250	19.05 - 35.56	n/a	50.01	38.10	76.20	38.10	19.10	1.0 - 0.07	PR Plus	R-6000/R-6600

* R6600 is not a Zero Halogen ribbon so should only be used in applications where a Zero Halogen solution is not required. Use R6000 where Zero Halogen solution is required.



HALOGEN FREE SOLUTION

B-7641 is a high grade, Halogen Free material. Used with the R-6000 ribbon it offers a complete Halogen Free Solution.