

# PRODUCT DATASHEET

## TRACK SP D75 25 W 3000 K 90RA NFL GY

TRACKLIGHT SPOT D75 25W | 3-phase tracklight spot with integrated control gear, low wattage



### AREAS OF APPLICATION

- Direct replacement for luminaires using HID lamps
- Accent lighting
- Fashion shops, accessories shops
- Retail
- Hotels, restaurants, shops

### PRODUCT BENEFITS

- Included 3-phase adapter compatible with common tracks (STAFF, NORLUX, GLOBAL, NUCO, NORDIC)
- Deep reflector and black antiglare ring for minimized glare (UGR <16)
- Reflector easily replaceable thanks to bayonet catch and rubber suction pad
- No distraction of attention from the illuminated objects thanks to reduced design
- Low flicker light thanks to special electronic control gear
- 5 years guarantee

### PRODUCT FEATURES

- Compact tracklight spot with integrated control gear
- Rotation angle: 350°, tilt angle: 90°
- Luminaire efficacy: up to 80 lm/W
- Available with color temperature 3000 K or 4000 K
- Very good color rendering index  $R_a$ : > 90
- Color rendering index  $R_{a9}$ : > 50



- Initial color consistency:  $\leq 3$  SDCM
- Equipped with reflectors with 24° beam angle
- Follows the unified LEDVANCE design language (SCALE design)
- Robust die-cast aluminum housing
- Available in matt white (like RAL9016), matt black (like RAL9004) and concrete grey (like RAL7042)

## TECHNICAL DATA

### Electrical data

|                        |                       |
|------------------------|-----------------------|
| Nominal wattage        | 25.00 W               |
| Operating mode         | Integrated LED driver |
| Nominal voltage        | 220...240 V           |
| Mains frequency        | 50/60 Hz              |
| Power factor $\lambda$ | $\geq 0.90$           |

### Luminaire control gear data

|  |    |
|--|----|
| Max. no. of lum. on circuit break. B16 A | 30 |
| Max. no. of lum. on circuit break. C10 A | 24 |
| Max. no. of lum. on circuit break. C16 A | 38 |


### Photometrical data

|                                      |               |
|--------------------------------------|---------------|
| Color temperature                    | 3000 K        |
| Color rendering index Ra             | >90           |
| Light color (designation)            | Warm White    |
| Luminous flux                        | 1750 lm       |
| Luminous efficacy                    | 75 lm/W       |
| Standard deviation of color matching | $\leq 3$ sdcM |

### Light technical data

|            |      |
|------------|------|
| Beam angle | 24 ° |
|------------|------|

### Dimensions & weight



|                       |          |
|-----------------------|----------|
| <b>Diameter</b>       | 75.0 mm  |
| <b>Height</b>         | 255.0 mm |
| <b>Product weight</b> | 770.00 g |

#### Colors & materials

|                       |                               |
|-----------------------|-------------------------------|
| <b>Housing color</b>  | Gray                          |
| <b>Product color</b>  | Gray                          |
| <b>Body material</b>  | Aluminum                      |
| <b>Cover material</b> | Polymethylmethacrylate (PMMA) |

#### Temperatures & operating conditions

|                                  |             |
|----------------------------------|-------------|
| <b>Ambient temperature range</b> | -10...40 °C |
|----------------------------------|-------------|

#### Lifespan

|                              |         |
|------------------------------|---------|
| <b>Lifespan L70 at 25 °C</b> | 50000 h |
| <b>Lifespan L80 at 25 °C</b> | 45000 h |
| <b>Lifespan L90 at 25 °C</b> | 30000 h |

#### Additional product data

|                          |                |
|--------------------------|----------------|
| <b>Mounting type</b>     | Surface        |
| <b>Mounting location</b> | Mounting track |



#### Capabilities

|                               |                   |
|-------------------------------|-------------------|
| <b>Dimmable</b>               | No                |
| <b>Type of connection</b>     | Adapter, 3-phasig |
| <b>LED module replaceable</b> | Not replaceable   |

#### Certificates & standards

|  |                             |
|--|-----------------------------|
| <b>Type of protection</b>                      | IP20                        |
| <b>Protection class</b>                        | II                          |
| <b>Protection class IK (shock resistance)</b>  | IK03                        |
| <b>Glow Wire Test according to IEC 695-2-1</b> | 650 °C                      |
| <b>Photobiological safety group EN62778</b>    | RG 1                        |
| <b>Standards</b>                               | CE/CB/ENEC/TÜV SÜD/EAC/RoHS |

Light Distribution



LDC typ cone

LDC typ polar

EQUIPMENT / ACCESSORIES

- Accessory reflectors with 15° or 38° beam angle available

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075113688 | Folding carton box<br>1      | 90 mm x 100 mm x 285 mm              | 830.00 g     | 2.57 dm <sup>3</sup>  |
| 4058075113695 | Shipping carton box<br>4     | 375 mm x 110 mm x 295 mm             | 3557.00 g    | 12.17 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

- ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.