



Lexmark XM7370

With output up to 70 ppm*, long-life imaging components, Ultra High Yield toner capacity, exceptional durability and complete finishing options, the XM7370 is Lexmark's large-workgroup monochrome leader.

Part Number

25B1204

Print Technology

Monochrome Laser

Function

Color Scanning, Copying, Faxing, Network Scanning, Printing

Workgroup Size

Large Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 10-inch (25 cm) class color touch screen

Print Speed (Letter, Black)

Up to 70 ppm⁶

Print Speed (Letter, Black) Duplex

Up to 42 spm⁶

Time to First Page (Black)

As fast as 4.0 seconds

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 300 x 300 dpi, 600 x 600 dpi

Copy Speed (Letter, Black)

Up to 70 cpm⁶

Copy Speed (Letter, Black) Duplex

Up to 44 spm⁶

Time to First Copy (Black)

As fast as 4.0 seconds

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Up to 72 / 75 sides per minute

A4/Ltr Simplex Scan Speed (Color)

Up to 72 / 75 sides per minute

A4/Ltr Duplex Scan Speed (Black)

Up to 144 / 150 sides per minute

A4/Ltr Duplex Scan Speed (Color)

Up to 144 / 150 sides per minute

Scan Area, Maximum

8.5 x 14.0 inches

ADF Scan

DADF (single pass Duplex)

Scanner Type

Flatbed scanner with ADF

Scan Technology

CCD

Optical Scanning Resolution

600 X 600 ppi (black), up to 600 X 600 ppi (color)

Scan File Formats (Send as)

JPEG, JPG, PDF, Secure PDF, TIFF, XPS, Archival PDF (A-1a, A-1b), Searchable PDF

Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Modem Speed

Max is 33,600 bps, V.34 Half-Duplex Kbps

Fax Transmission Speed

< 3 seconds per page

Processor

Quad Core, 1200 MHz

Memory, Standard

2048 MB

Memory, Maximum

6144 MB

Hard Disk

Included in configuration

Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12)

Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported

Debian GNU/Linux 7.0, 8.0, SUSE Linux Enterprise Server 10, 11, 12, openSUSE Linux 13.2, Ubuntu 16.04 LTS, Fedora 23, 24, Red Hat Enterprise Linux WS 6, 7, openSUSE Linux 42.3

Microsoft Windows Operating Systems Supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows 10

Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell Open Enterprise Server on SUSE Linux Enterprise Server, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4, Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11, Novell Open Enterprise Server 2 SP2 on SuSE Linux Enterprise Server 10 SP3 3

UNIX Operating Systems Supported

Sun Solaris x86 10, 11, Sun Solaris SPARC 10, 11, IBM AIX 6.1, 7.1

Included Paper Handling

550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex, 550-Sheet Tray

Optional Paper Handling

550-Sheet Tray, 2100-Sheet Tray

Paper Input Capacity, Standard

Up to 1200 pages 20 lb or 75 gsm bond

Paper Input Capacity, Maximum

Up to 2300 pages 20 lb or 75 gsm bond

Paper Output Capacity, Standard

Up to 550 pages 20 lb or 75 gsm bond

Paper Output Capacity, Maximum

Up to 1050 pages 20 lb or 75 gsm bond

Paper Weight Range Supported - Standard Tray (lb.)

16 - 47 lb.

Integrated Tray Card Stock Upper limit (grain short)

Cover - 176 gsm (65 lb), Index Bristol - 199 gsm (110 lb), Tag - 203 gsm (125 lb)

ADF

200-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Up to 200 pages 20 lb or 75 gsm bond

ADF Paper Output Capacity

Up to 200 pages 20 lb or 75 gsm bond

Finishing Option

Yes

Number of Paper Inputs, Standard

3

Number of Paper Inputs, Maximum

6

Media Types Supported

Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide.

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Standard Ports

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified Port (Type A)

Optional Local Ports

Internal RS-232C serial, Internal 1284-B
Bidirectional Parallel

Optional Network Ports

Marknet N8370 WiFi Option, MarkNet N8230
Fiber Ethernet Print Server, Marknet N8372 WiFi
Option

Direct USB

Yes

Ethernet Network

Yes

Network Protocol Support

TCP/IP IPv4, AppleTalk™, TCP/IP IPv6, TCP, UDP

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port
9400), FTP, TFTP, ThinPrint .print integration,
Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c,
SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA
(AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS,
mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5,
MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printable Area

0.167 inches of the top, bottom, right and left
edges (within)

Printer Languages (Standard)

PCL 5e Emulation, PCL 6 Emulation, Personal
Printer Data Stream (PPDS), PostScript 3
Emulation, Direct Image, Microsoft XPS (XML
Paper Specification), AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular
and Wide, 158 scalable PostScript fonts, 2 PCL
bitmap fonts, 39 scalable PPDS fonts, 5 PPDS
bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-
B scalable PCL 5e fonts, For more information,
refer to the Technical Reference.

Laser Cartridge Yields (up to)⁵

45,000-page Extra High Yield Cartridge,

Imaging Unit Estimated Yield

Up to 150000 pages, based on 3 average letter/
A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

11,000-page Starter Return Program Toner
Cartridge

Replacement Cartridges:

Product functions only with replacement
cartridges designed for use in a specific
geographical region. See www.lexmark.com/
regions for more details.

Packaged Size (in. - H x W x D)

53.7 x 30.0 x 32.7 in.

Packaged Weight (lb.)

222.66 lb.

Size (in. - H x W x D)

45.3 x 27.0 x 27.3 in.

Weight (lb.)

147.6 lb.

Noise Level, Idle

14 dBA

Noise Level (Print), Operating

56 dBA

Duplex Print Noise Level, Operating

55 dBA

Noise Level (Copy), Operating

59 dBA

Noise Level (Scan), Operating

57 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.2 watts

Average Power (Sleep Mode)

3.1 watts

Average Power (Ready Mode)

50 watts

Average Power (Printing)

850 watts

Average Power (Copying)

900 watts

Average Power (Scanning)

86 watts

ENERGY STAR Typical Electricity Consumption (TEC)

3.4 kilowatt-hours per week

Limited Warranty - See Statement of Limited Warranty

1-Year Onsite Repair, Next Business Day

Product Certifications

ENERGY STAR, Blue Angel RAL-UZ-171, ICES-003
Class A, BSMI Class A, VCCI Class A, US FDA/
CDRH, UL 60950-1, FCC Class A, cUL CAN/CSA-
C22.2 60950-1, NOM, MET-I, IEC 60825-1, CB
EN/IEC 60950-1, CB EN/IEC 60825-1, CCD-035,
CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC
60950-1, CE EN/IEC 60825-1, EN 61000-3, EN
55022 Class A, EuP, EN 55024, UL), EFTA (CE),
CISPR 22 Class A, KCC, CCC, CECP, CEL, A-tick
DoC, C-tick CoC, UL-AR, KC mark, UL GS mark,
ISO 532B, ECMA-370, TED, GOST-R, SII, TER, Bel
GISS

Maximum Monthly Duty Cycle

Up to 350000 pages per month³

Recommended Monthly Page Volume

5000 - 100000 pages²

Specified Operating Environment

Humidity: 8 to 80% Relative Humidity,
Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 -
2896 Meters (9,500 Feet)

License/Agreement Terms

Printers are sold subject to certain license/
agreement conditions. See www.lexmark.com/
printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212110

Harmonized Tariff Code

8443.31.0000

¹This product includes software developed by the OpenSSL
Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

²"Recommended Monthly Page Volume" is a range of pages that
helps customers evaluate Lexmark's product offerings based
on the average number of pages customers plan to print on the
device each month. Lexmark recommends that the number of
pages per month be within the stated range for optimum device
performance, based on factors including: supplies replacement
intervals, paper loading intervals, speed, and typical customer
usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum
number of pages a device could deliver in a month using a

multishift operation. This metric provides a comparison of
robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device
speed, paper size and feed orientation, toner coverage, tray
source, percentage of black-only printing and average print job
complexity.

⁵Average yield at approximately 5% print coverage per colour.

⁶Print and copy speeds measured in accordance with ISO/
IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more
information see: www.lexmark.com/ISOspeeds.

P/N Toner Cartridges

58D0Z00 Lexmark 58D0Z00 Black Return
Program Imaging Unit
25B3090 Lexmark 25B3090 Black Toner
Cartridge

P/N Paper Handling

50G0801 250-Sheet Tray
25B2900 550-Sheet Tray
25B2950 2100-Sheet Tray
25B2999 500-Sheet Offset Stacker
50G0849 Staple, Hole Punch Finisher
50G0850 Staple Finisher
50G0852 4-Bin Mailbox

P/N Memory Options

57X9801 256MB Flash Memory Card
57X9814 Korean Font Card
57X9815 Japanese Font Card
57X9812 Simplified Chinese Font Card
57X9810 Traditional Chinese Font Card
57X0204 4GBx32 DDR3-DRAM

P/N Application Solutions

40C9201 Card for IPDS
40C9200 Forms and Bar Code Card
40C9202 Card for PRESCRIBE Emulation
57X0300 Contact Authentication Device
57X0301 Contactless Authentication Device

P/N Connectivity

27X0142 Lexmark MarkNet™ N8230 Fiber
Ethernet Print Server
27X6410 Lexmark MarkNet N8372 802.11 a/b/
g/n/ac Wireless Print Server
27X6510 MarkNet N8370 802.11 a/b/g/n/ac
Wireless Print Server
57X7030 English Keyboard Kit
57X7040 English Keyboard Kit
1021231 Parallel Cable (10-foot)
1021294 USB Cable (2-meter)
14F0100 RS-232C Serial Interface Card
14F0000 Parallel 1284-B Interface Card