




### Model Number

NBB0,6-4GM22-E2

### Features

- 0.6 mm embeddable
- Miniature design

### Connection




### Accessories

#### BF 4

Mounting flange, 4 mm

### Dimensions



### Technical Data

#### General specifications

Switching element function	PNP	NO
Rated operating distance	$s_n$	0.6 mm
Installation	embeddable	
Output polarity	DC	
Assured operating distance	$s_a$	0 ... 0.486 mm
Reduction factor $r_{Al}$	0.4	
Reduction factor $r_{Cu}$	0.29	
Reduction factor $r_{304}$	0.76	
Reduction factor $r_{Brass}$	0.46	

#### Nominal ratings

Operating voltage	$U_B$	10 ... 30 V
Switching frequency	$f$	0 ... 1400 Hz
Hysteresis	$H$	typ. 5%
Reverse polarity protected	reverse polarity protected	
Short-circuit protection	pulsing	
Voltage drop	$U_d$	$\leq 3$ V
Operating current	$I_L$	0 ... 100 mA
Off-state current	$I_r$	0 ... 0.1 mA typ. at 25 °C
No-load supply current	$I_0$	$\leq 10$ mA
Indication of the switching state	LED, yellow	

#### Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

#### Mechanical specifications

Connection type	cable PUR, 2 m
Core cross-section	0.055 mm <sup>2</sup>
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	PC
Protection degree	IP67

#### Compliance with standards and directives

Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

#### Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Products with a maximum operating voltage of $\leq 36$ V do not bear a CCC marking because they do not require approval.