

8-Port Rack-Mount PDU with C13 Outlets - 16 A - 10 ft. Power Cord (CEE7/7) - 1U

Product ID: PDU08C13EU



This rack-mount PDU features eight C13 outlets and you can install it into 1U of rack space to power your rack-mount equipment. The PDU provides 16 amps of power to be shared across the eight outlets.

Unlike some rack power solutions that mount awkwardly if at all, this rack-mount PDU is EIA-310D compliant, which ensures a secure and tidy installation into any 19" rack with 1U of available space. Mounting screws and cage nuts are also included to ensure you have everything you need, saving you time and hassle.

For maximum compatibility with your devices, this PDU features C13 outlets which are ideal for a wide range of globally distributed devices including I.T equipment, office equipment, measuring instruments and medical devices. Plus, with a total of eight C13 outlets, the PDU can distribute power to your entire rack.

In the event of random energy surges that can occur during power outages or other anomalies, this PDU prevents costly damages to your equipment with a built-in dual circuit breaker, ensuring your equipment is protected.

The housing of this PDU is also constructed of rugged steel to provide maximum durability in any environment.

The PDU08C13EU is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Add eight easily accessible power outlets to your server rack
- Provide power to rack-mounted equipment with C13 power plugs

Features

- Ensure hassle-free installation with a 1U EIA-310D compliant PDU
- Get wide device compatibility with a PDU that features C13 outlets
- 10 ft. (3 m) C19 to CEE7/7 power cord included
- Protect your equipment with the dual circuit breaker that's built into this PDU
- Solid steel chassis for durability
- 1U rack-mount design

Hardware

Warranty	2 Years
Form Factor	Horizontal
Number of Power Outlets	8
Rack-Mountable	Yes

Performance

General Specifications	Surge Protection: 3600 Joules
	Phase Power: Single phase power adapter
	Power Cord Included: 10 ft [3 m] C19 to CEE7/7
Maximum Total Current	16A
Maximum Total Current Draw per Phase	16A
Regulatory Derated Input Current (North America)	16A
Nominal Input Voltage	110V - 240V
Nominal Output Voltage	110V - 240V
Maximum Output Voltage	240V
Load Capacity	3840 VA

Connector(s)

Input Connector(s)	IEC C20 (16A, 3 conductor) Power
Output Connectors	IEC C13 (10A, 3 conductor) Power Receptacle



Power

Input Voltage	110V-240V AC
---------------	--------------

Physical Characteristics

Material	Steel
Product Length	3.9 in [100 mm]
Product Width	18.9 in [48 cm]
Product Height	1.7 in [44 mm]
Weight of Product	4.4 lb [2.0 kg]

Packaging Information

Package Length	21.7 in [55 cm]
Package Width	7.5 in [19 cm]
Package Height	3.2 in [82 mm]
Shipping (Package) Weight	4.9 lb [2.2 kg]

What's in the Box

Included in Package	<ul style="list-style-type: none"> rack-mount PDU 10 ft [3 m] C19 to CEE7/7 power cord M5 screws M5 cage nuts instruction manual
---------------------	---

****Product appearance and specifications are subject to change without notice.***

