



### Model Number

**NBB8-18GM50-E2-3G-3D**

### Features

- Increased operating distance
- 8 mm flush
- ATEX-approval for zone 2 and zone 22

### Accessories

#### BF 18

Mounting flange, 18 mm

#### EXG-18

Quick mounting bracket with dead stop

## Technical Data

### General specifications

|                            |       |                    |
|----------------------------|-------|--------------------|
| Switching function         |       | Normally open (NO) |
| Output type                |       | PNP                |
| Rated operating distance   | $s_n$ | 8 mm               |
| Installation               |       | flush              |
| Output polarity            |       | DC                 |
| Assured operating distance | $s_a$ | 0 ... 6.48 mm      |
| Reduction factor $r_{AI}$  |       | 0.45               |
| Reduction factor $r_{CU}$  |       | 0.4                |
| Reduction factor $r_{304}$ |       | 0.7                |
| Output type                |       | 3-wire             |

### Nominal ratings

|                             |       |                            |
|-----------------------------|-------|----------------------------|
| Operating voltage           | $U_B$ | 10 ... 30 V DC             |
| Switching frequency         | $f$   | 0 ... 500 Hz               |
| Hysteresis                  | $H$   | typ. 5 %                   |
| Reverse polarity protection |       | reverse polarity protected |
| Short-circuit protection    |       | pulsing                    |
| Voltage drop                | $U_d$ | $\leq 3$ V                 |

### Design data

|                                |       |  |
|--------------------------------|-------|--|
| Operating current              | $I_L$ | 0 ... 200 mA                           |
| Off-state current              | $I_r$ | 0 ... 0.5 mA typ. 0.1 $\mu$ A at 25 °C |
| No-load supply current         | $I_0$ | $\leq 15$ mA                           |
| Time delay before availability | $t_v$ | $\leq 20$ ms                           |
| Switching state indicator      |       | LED, yellow                            |

### Functional safety related parameters

|                                |        |
|--------------------------------|--------|
| MTTF <sub>d</sub>              | 2240 a |
| Mission Time (T <sub>M</sub> ) | 20 a   |
| Diagnostic Coverage (DC)       | 0 %    |

### Ambient conditions

|                     |                                |
|---------------------|--------------------------------|
| Ambient temperature | -25 ... 70 °C (-13 ... 158 °F) |
|---------------------|--------------------------------|

### Mechanical specifications

|                      |                       |
|----------------------|-----------------------|
| Connection type      | cable PVC , 2 m       |
| Core cross-section   | 0.34 mm <sup>2</sup>  |
| Housing material     | brass, nickel-plated  |
| Sensing face         | PBT                   |
| Degree of protection | IP66 / IP67           |
| Cable                |                       |
| Bending radius       | > 10 x cable diameter |

### General information

|                           |                         |
|---------------------------|-------------------------|
| Use in the hazardous area | see instruction manuals |
| Category                  | 3G; 3D                  |


### Compliance with standards and directives

|                     |   |
|---------------------|---|
| Standard conformity |   |
| Standards           | EN 60947-5-2:2007<br>IEC 60947-5-2:2007 |


### Approvals and certificates

|              |  |
|--------------|--|
| UL approval  | cULus Listed, General Purpose                                      |
| CSA approval | cCSAus Listed, General Purpose                                     |
| CCC approval | CCC approval / marking not required for products rated $\leq 36$ V |

## Dimensions




## Electrical Connection



**Equipment protection level Gc (nA)**

|             |   |
|-------------|---|
| Certificate | PF 15CERT3754 X   |
| CE marking  |  |

|              |  |
|--------------|--|
| ATEX marking |  II 3G Ex nA IIC T6 Gc<br>The Ex-related marking can also be printed on the enclosed label. |
|--------------|--|

|           |  |
|-----------|--|
| Standards | EN 60079-0:2012+A11:2013, EN 60079-15:2010<br>Ignition protection category "n"<br>Use is restricted to the following stated conditions |
|-----------|--|

**Special conditions**


Maximum operating current  $I_L$  The maximum permissible load current must be restricted to the values given in the following list. High load currents and load short-circuits are not permitted.

Maximum operating voltage  $U_{Bmax}$  The maximum permissible operating voltage  $U_{Bmax}$  is restricted to the values in the following list. Tolerances are not permissible.

Maximum permissible ambient temperature  $T_{Umax}$  dependant of the load current  $I_L$  and the max. operating voltage  $U_{Bmax}$   
Information can be taken from the following list.

|   |                  |
|---|------------------|
| at $U_{Bmax}=30\text{ V}$ , $I_L=200\text{ mA}$ | 47 °C (116.6 °F) |
| at $U_{Bmax}=30\text{ V}$ , $I_L=100\text{ mA}$ | 52 °C (125.6 °F) |

**Equipment protection level Dc**

|            |   |
|------------|---|
| CE marking |  |
|------------|---|

|              |   |
|--------------|---|
| ATEX marking |  II 3D IP67 T 92 °C (197.6 °F) X |
|--------------|---|


|           |  |
|-----------|--|
| Standards | EN 50281-1-1<br>Protection via housing<br>Use is restricted to the following stated conditions |
|-----------|--|


**Special conditions**

Maximum heating (Temperature rise) dependant of the load current  $I_L$  and the max. operating voltage  $U_{Bmax}$   
Information can be taken from the following list. The maximum surface temperature at maximum ambient temperature is given in the Ex identification of the apparatus.

|   |      |
|---|------|
| at $U_{Bmax}=30\text{ V}$ , $I_L=200\text{ mA}$ | 22 K |
| at $U_{Bmax}=30\text{ V}$ , $I_L=100\text{ mA}$ | 18 K |

**Equipment protection level Dc (tc)**

|            |   |
|------------|---|
| CE marking |  |
|------------|---|

|              |   |
|--------------|---|
| ATEX marking |  II 3D Ex tc IIIC T80°C Dc<br>The Ex-related marking can also be printed on the enclosed label. |
|--------------|---|

|           |  |
|-----------|--|
| Standards | EN 60079-0:2012+A11:2013, EN 60079-31:2014<br>Protection by enclosure "tc" Some of the information in this instruction manual is more specific than the information provided in the datasheet. |
|-----------|--|

General The corresponding datasheets, declarations of conformity, EC-type examination certificates, certifications, and control drawings, where applicable (see datasheets), form an integral part of this document. These documents can be found at [www.pepperl-fuchs.com](http://www.pepperl-fuchs.com). The maximum surface temperature of the device was determined without a layer of dust on the apparatus. Some of the information in this instruction manual is more specific than the information provided in the datasheet.

**Special conditions**

Maximum permissible ambient temperature  $T_{Umax}$  dependant of the load current  $I_L$  and the max. operating voltage  $U_{Bmax}$   
Information can be taken from the following list.

|   |                  |
|---|------------------|
| at $U_{Bmax}=30\text{ V}$ , $I_L=200\text{ mA}$ | 47 °C (116.6 °F) |
| at $U_{Bmax}=30\text{ V}$ , $I_L=100\text{ mA}$ | 52 °C (125.6 °F) |