

DIN rail, unperforated - NS 35/15 AL UNPERF 250MM - 1207659

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail, unperforated, Standard profile, width: 35 mm, height: 15 mm, in acc. with EN 60715: 2001, material: Aluminum, uncoated, length: 250 mm, color: silver

RoHS

Key Commercial Data

Packing unit	1
GTIN	
GTIN	4046356366571
Custom tariff number	76042990

Technical data

Dimensions

Height	15 mm
Length	250 mm
Width	35 mm
Hole width	0.00 mm
Hole height	0.00 mm
Drill hole spacing	0.00 mm

General

Material	Aluminum
Coating	uncoated
Color	silver
Max. permissible thermal nominal current for PEN function	192.00 A

Standards and Regulations

DIN rail, unperforated - NS 35/15 AL UNPERF 250MM - 1207659

Technical data

Standards and Regulations


Test standard	in acc. with EN 60715: 2001
---------------	-----------------------------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 4.0	27110804
eCl@ss 4.1	27110804
eCl@ss 5.0	27141143
eCl@ss 5.1	27141143
eCl@ss 6.0	27141143
eCl@ss 7.0	27141143
eCl@ss 8.0	27400602
eCl@ss 9.0	27400602

ETIM

ETIM 3.0	EC001285
ETIM 4.0	EC000212
ETIM 5.0	EC000212
ETIM 6.0	EC001285

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708

DIN rail, unperforated - NS 35/15 AL UNPERF 250MM - 1207659

Classifications

UNSPSC

UNSPSC 13.2	39121708
-------------	----------