

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail, unperforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715: 2001, material: Aluminum, uncoated, length: 2000 mm, color: silver

Why buy this product

- The slide nuts even enable components without an additional snap-on foot to be mounted
- The NS 35/15 AL DIN rail is designed to accommodate GLM ... slide nuts

Key Commercial Data

Packing unit	2 M
Minimum order quantity	5 M
GTIN	 4 017918 017477
GTIN	4017918017477
Weight per Piece (excluding packing)	355.000 g
Custom tariff number	76042990
Country of origin	Germany

Technical data

Dimensions

Height	15 mm
Length	2000 mm
Width	35 mm
Hole width	0.00 mm
Hole height	0.00 mm
Drill hole spacing	0.00 mm

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

Technical data

General

Material	Aluminum
Coating	uncoated
Color	silver
Max. permissible thermal nominal current for PEN function	192.00 A

Standards and Regulations


Test standard	similar to EN 60715: 2001
Connection in acc. with standard	IEC/EN

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 4.0	23150301
eCl@ss 4.1	23150301
eCl@ss 5.0	27141143
eCl@ss 5.1	27141143
eCl@ss 6.0	27141143
eCl@ss 7.0	27141143
eCl@ss 8.0	27400602
eCl@ss 9.0	27400602

ETIM

ETIM 2.0	EC001285
ETIM 3.0	EC001285
ETIM 4.0	EC000212

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

Classifications

ETIM

ETIM 5.0	EC000212
ETIM 6.0	EC001285

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708