

## DIN rail perforated - NS 35/15 PERF 1155MM - 1207695


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail perforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715: 2001, material: Steel, galvanized, passivated with a thick layer, length: 1155 mm, color: silver



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 STK                                                                                                   |
| Minimum order quantity               | 10 STK                                                                                                  |
| GTIN                                 | <br>4 017918 936020 |
| GTIN                                 | 4017918936020                                                                                           |
| Weight per Piece (excluding packing) | 710.000 g                                                                                               |
| Custom tariff number                 | 72166190                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|                    |          |
|--------------------|----------|
| Height             | 15 mm    |
| Length             | 1155 mm  |
| Width              | 35 mm    |
| Hole width         | 15.00 mm |
| Hole height        | 6.20 mm  |
| Drill hole spacing | 25.00 mm |

#### General

|          |                                           |
|----------|-------------------------------------------|
| Material | Steel                                     |
| Coating  | galvanized, passivated with a thick layer |
| Color    | silver                                    |

# DIN rail perforated - NS 35/15 PERF 1155MM - 1207695


## Technical data

### Standards and Regulations

|                                  |                           |
|----------------------------------|---------------------------|
| Test standard                    | similar to EN 60715: 2001 |
| Connection in acc. with standard | IEC/EN                    |

## Drawings

Dimensional drawing



## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 23150301 |
| eCl@ss 4.1 | 23150301 |
| eCl@ss 5.0 | 27141143 |
| eCl@ss 5.1 | 27141143 |
| eCl@ss 6.0 | 27141143 |
| eCl@ss 7.0 | 27141143 |
| eCl@ss 8.0 | 27400602 |
| eCl@ss 9.0 | 27400602 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC001285 |
| ETIM 3.0 | EC001285 |
| ETIM 4.0 | EC000212 |
| ETIM 5.0 | EC000212 |
| ETIM 6.0 | EC001285 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30212109 |
| UNSPSC 7.0901 | 39121708 |

## DIN rail perforated - NS 35/15 PERF 1155MM - 1207695

### Classifications

#### UNSPSC

|              |          |
|--------------|----------|
| UNSPSC 11    | 39121708 |
| UNSPSC 12.01 | 39121708 |
| UNSPSC 13.2  | 39121708 |