



AOC P2 Q32P2 computer monitor 80 cm (31.5") 2560 x 1440 pixels 2K Ultra HD LED Black

Brand : AOC

Product family: P2

Product code: Q32P2

Product name : Q32P2

Q32P2 - Comfort, quality and productivity in a 31.5" QHD display

[AOC P2 Q32P2 computer monitor 80 cm \(31.5"\) 2560 x 1440 pixels 2K Ultra HD LED Black:](#)

Comfort, quality and productivity in a 31.5" QHD display

The Q32P2 features a flat 31.5" IPS panel with QHD resolution. Perfect for professionals and home offices, it ensures ultimate comfort and maximum productivity with its 180° swivel, its Low Blue Light technology, and the USB hub.

AOC P2 Q32P2. Display diagonal: 80 cm (31.5"), Display resolution: 2560 x 1440 pixels, HD type: 2K Ultra HD, Display technology: LED, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	80 cm (31.5")	Headphone connectivity	3.5 mm
Display brightness (typical)	250 cd/m ²	DC-in jack	✗
Display resolution *	2560 x 1440 pixels	Ergonomics	
Native aspect ratio *	16:9	Panel mounting interface	100 x 100 mm
Response time	4 ms	Cable lock slot *	✗
HD type *	2K Ultra HD	VESA mounting *	✓
Display technology *	LED	Height adjustment *	✓
Backlight type	W-LED	Height adjustment	15 cm
Display surface	Matt	Pivot	✓
Screen shape *	Flat	Pivot angle	0 - 180°
Supported graphics resolutions	1920 x 1080 (HD 1080), 2560 x 1440	Swivelling	✓
Supported video modes	1080p, 1440p	Swivel angle range	-175 - 175°
Aspect ratio	4:3, 16:9	Tilttable	✓
Contrast ratio (typical) *	1000:1	Tilt angle range	-4 - 20.5°
Contrast ratio (dynamic)	50000000:1	On Screen Display (OSD)	✓
Maximum refresh rate *	75 Hz	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, SER
Viewing angle, horizontal	178°	Number of OSD languages	16
Viewing angle, vertical	178°	Plug and Play	✓
Display number of colours *	1.073 billion colours	Power	
Panel type *	IPS	Energy efficiency class (SDR) *	F
Pixel pitch	0.2737 x 0.2737 mm	Energy consumption (SDR) per 1000 hours *	32 kWh
Viewable size, horizontal	69.8 cm	Power consumption (typical) *	35 W
Viewable size, vertical	39.3 cm	Power consumption (standby) *	0.5 W
Surface hardness	3H	Power consumption (off)	0.3 W
Colour depth	10 bit	AC input voltage	100 - 240 V
sRGB coverage (typical)	102%		
Adobe RGB coverage	75%		
Performance			
NVIDIA G-SYNC *	✗		

Performance		Power	
AMD FreeSync *	✗	AC input frequency	50/60 Hz
VESA Adaptive Sync support	✓	External power adapter	✗
Flicker-free technology	✓	Energy efficiency scale	A to G
Low Blue Light technology	✓	Operational conditions	
Multimedia		Operating temperature (T-T)	0 - 40 °C
Built-in speaker(s) *	✓	Storage temperature (T-T)	-20 - 55 °C
Number of speakers	2	Operating relative humidity (H-H)	10 - 85%
RMS rated power	3 W	Storage relative humidity (H-H)	5 - 93%
Built-in camera *	✗	Weight & dimensions	
Design		Width (with stand)	730.2 mm
Market positioning *	Business	Depth (with stand)	275.1 mm
Product colour *	Black	Height (with stand)	650.6 mm
Front bezel colour	Black	Weight (with stand)	9.5 kg
Detachable stand	✓	Width (without stand)	73 mm
Feet colour	Black	Depth (without stand)	5.77 cm
Heavy metals free	Hg (mercury)	Height (without stand)	43.4 cm
Ports & interfaces		Packaging data	
Built-in USB hub *	✓	Stand included	✓
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Cables included	DisplayPort,HDMI
USB Type-A downstream ports quantity	4	DisplayPort cable length	1.8 m
DVI port	✗	HDMI cable length	1.8 m
HDMI *	✓	Package width	835 mm
HDMI ports quantity	2	Package depth	225 mm
HDMI version	1.4	Package height	545 mm
DisplayPorts quantity	1	Package weight	12.3 kg
DisplayPort version	1.2	Package type	Box
Audio input	✗	Other features	
Headphone out *	✓	Recyclable packaging material	100%
Headphone outputs	1	Mean time between failures (MTBF)	50000 h



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.