


Blade receptable

Blade Receptacles, Fully Insulated, RND



SPECIFICATION:

| | |
|------------------|------------|
| Material | Brass |
| Surface material | Tin-plated |

PRODUCT RANGE:

| Art. Nr. | Contact | Cross-section | Colour | Insulation material | Temperature range | Voltage | Thickness |
|---------------|--------------|---------------------------|--------|---------------------|-------------------|---------|-----------|
| RND 465-00067 | 6.3 x 0.8 mm | 0.5...1.5 mm ² | red | Nylon | max. +105 °C | 600 V | 0.4 mm |
| RND 465-00069 | 2.8 x 0.5 mm | 0.5...1.5 mm ² | red | Nylon | max. +105 °C | 600 V | 0.3 mm |
| RND 465-00070 | 2.8 x 0.8 mm | 0.5...1.5 mm ² | red | Nylon | max. +105 °C | 600 V | 0.3 mm |
| RND 465-00071 | 6.3 x 0.8 mm | 1.5...2.5 mm ² | blue | Nylon | max. +105 °C | 600 V | 0.4 mm |
| RND 465-00072 | 6.3 x 0.8 mm | 4...6 mm ² | yellow | Nylon | max. +105 °C | 600 V | 0.4 mm |