


Piggyback terminal

Piggyback Terminals, Insulated















SPECIFICATION:

Material	Brass
Surface material	Tin-plated
Voltage	600 V

PRODUCT RANGE:

Art. Nr.	Contact	Cross-section	Colour	Insulation material	Temperature range	Thickness
RND 465-00079	6.3 x 0.8 mm	0.5...1.5 mm ²	red	Vinyl	max. +105 °C	0.4 mm
RND 465-00081	6.3 x 0.8 mm	4...6 mm ²	yellow	Vinyl	max. +105 °C	0.4 mm
RND 465-00087	6.3 x 0.8 mm	1.5...2.5 mm ²	blue	Vinyl	max. +105 °C	0.4 mm

Products Operation Instruction

Products type	Vinyl insulated double crimp disconnectors (1mm ²)	Products type																						
Wire Size Range	22 ~16 AWG	<p>1. Use tool to strip a suitable length of insulation from the wire.</p> 	<p>2. Insert the wires (stripped end) into the terminals wire port.</p> 		<p>Height & Width after crimping</p> <table border="1"> <thead> <tr> <th>Wire Size</th> <th>Height (mm)</th> <th>Width (mm)</th> </tr> </thead> <tbody> <tr> <td>22AWG</td> <td>3.60</td> <td>5.50</td> </tr> <tr> <td>20AWG</td> <td>3.60</td> <td>5.50</td> </tr> <tr> <td>18AWG</td> <td>3.60</td> <td>5.50</td> </tr> <tr> <td>16AWG</td> <td>3.60</td> <td>5.50</td> </tr> </tbody> </table>					Wire Size	Height (mm)	Width (mm)	22AWG	3.60	5.50	20AWG	3.60	5.50	18AWG	3.60	5.50	16AWG	3.60	5.50
Wire Size	Height (mm)									Width (mm)														
22AWG	3.60	5.50																						
20AWG	3.60	5.50																						
18AWG	3.60	5.50																						
16AWG	3.60	5.50																						
Wire strip Length	6.80mm	<p>3. Use the clamps to keep pressure on the connector (terminals must be placed in the right position).</p>  	<p>4. Done.</p> 																					
Crimping Tool																								