

Thin Wall Heat-Shrink Tubing

Features

- Thin-wall tubing
- Crosslinked Polyolefin
- Shrink ratio: 2:1
- Flame retardant
- High flexibility
- UV Resistant
- Flexible, flame retardant, low shrinking temperature
- Free from harmful substances such as PBB's, PBBO's, PBBE's



Specification

Material	Cross-linked Polyolefin
Shrink Ratio	2:1
Minimum Shrink Temperature	70 °C
Service Temperature Range	-55 ... 135°C
Colour	Black
Dielectric Strength	>20 kV
Flammability Rating	UL-VW1
Minimum Full Recovery Temperature:	100 °C
Longitudinal Change	0 ± 10% max.

Product Range

Type	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Length (meter)
RND 465-01198	3.2	1.6	0.48	1.2
RND 465-01199	4.8	2.4	0.48	1.2
RND 465-01200	6.4	3.2	0.56	1.2
RND 465-01201	9.5	4.8	0.62	1.2
RND 465-01202	12.7	6.4	0.62	1.2
RND 465-01203	19.0	9.5	0.68	1.2
RND 465-01204	25.4	12.7	0.87	1.2
RND 465-01205	38.1	19.0	1.00	1.2
RND 465-01206	50.8	25.4	1.10	1.2