

Heavy Wall Heat-Shrink Tubing

Features

- Heavy-wall tubing
- Good environmental protection
- Good electrical and mechanical performance
- Ideal for low voltage applications
- UV resistant
- Recommended for applications on light cables and wire harnesses which require waterproofing, protection of connector components.
- Halogen and Cadmium free



Specification

Material	Polyolefin, Matt Surface
Shrink Ratio	3:1 ... 4:1
Shrink Temperature	120 °C
Service Temperature Range	-55 ... 110°C
Colour	Black
Dielectric Strength	>20 kV
Longitudinal Change	0 ± 10 % max.

Product Range

Type	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Standard length in m
RND 465-01207	9.0	3.0	1.8	1.22
RND 465-01208	16.0	4.0	2.2	1.22
RND 465-01209	22.0	6.0	2.7	1.22
RND 465-01210	34.0	8.0	3.2	1.22
RND 465-01211	43.0	12.0	4.0	1.22
RND 465-01212	55.0	16.0	4.0	1.22
RND 465-01213	75.0	22.0	4.0	1.22
RND 465-01214	85.0	25.0	4.2	1.22