



PIN ASSIGNMENT:

P1	_____	P2
1	_____	1
2	_____	2
3	_____	3
4	_____	4
5	_____	5
6	_____	6
7	_____	7
8	_____	8
9	_____	9
SHELL	_____	SHELL

NOTES:
ELECTRICAL CHARACTER:
 1.100% OPEN&SHORTTESTING.
 2.ROHS and REACH COMPLIANT.
 3. Copper OD Toleranle +/- 0.02mm
 4.connector connection method: soldering.
 5.THIS PRODUCT INCLUDED THE RAW MATERIAL:

PVC ` COPPER WIRE ` Gold-plated PBT ` solder wire
 copper ` nickel-plated copper
 ` nickel plated Iron shell `

Temperature Range: 10°C...60°C

Product Number	CU.P/NO	Length+/- (mm)	Packing
301-16-446	RND 765-00031	1800+/-10mm	1pc/poly bag with single color printed RND Connect logo++ RND Label

NO	ITEM	DESCRIPTION
C	CONNECTOR 2	DB 9P MALE NICKEL-PLATED
B	CONNECTOR 1	DB 9P MALE NICKEL-PLATED
A	CABLE	9C+1 28AWG(7X0.12BC) +D7X0.12BC +AL/MYLAR OD5.0MM color:BEIGE