

3-Port Portable USB 3.0 Hub plus Gigabit Ethernet - Aluminum with Built-in Cable

Product ID: ST3300GU3B



The ST3300GU3B Portable USB 3.0 Hub is TAA compliant features an integrated GbE port, enabling you to expand your laptop connectivity by adding three external USB 3.0 ports, as well as a Gigabit network port via a single USB 3.0 connection. This hub is an ideal laptop accessory for your Microsoft Surface Pro 4, Surface Pro 3, Surface Book, Dell XPS 13, and many other devices.

The hub merges Gigabit network support and USB 3.0 hub access into lightweight yet sturdy aluminum casing, providing vital connectivity ports that are often limited or nonexistent on modern mobile computers, while remaining compact and travel-friendly. Plus, with an attached USB 3.0 host connection cable there's no need to carry a separate cable with you, so you can tuck the hub neatly into your laptop bag for maximum portability.

For faster and more consistent network connections, the integrated Ethernet port leverages the 5Gbps capabilities of the USB 3.0 interface to provide wired Gigabit access that is fully compatible with IEEE 802.3/u/ab standards. Plus, the GbE port supports Wake-on-LAN (WOL), so you can remotely wake your computer over your network.

An ideal laptop accessory, this mobile USB hub is great for connecting low-power peripherals like a mouse, keyboard or USB flash drive, and also includes a universal power adapter for connecting devices such as .

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Work from your Ultrabook, laptop or netbook easily while you're on the run or on the road, the perfect travel accessory with more connectivity options
- An ideal laptop accessory for Microsoft Surface Pro 4, Surface Pro 3, Surface Book, Dell XPS 13, Dell Latitude 11 5000 Series 2-in-1 and other devices



- Connect a wide variety of peripherals at home / office to a laptop, all from a single USB 3.0 connection
- Add Gigabit support to your laptop for use in boardrooms, hotels, classrooms, offices, or home environments
- Replace a failed built-in Ethernet port on a laptop, or upgrade to 1000 Mbps Gigabit connectivity

Features

- TAA Compliant
- Provides three USB 3.0 hub ports, with support for up to 5 Gbps
- Gigabit Ethernet port (RJ45) with Wake-on-LAN (WOL) support
- Aluminum casing with a compact, slim, and lightweight design for maximum portability
- Dongle-style combination adapter with built-in USB 3.0 cable
- IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az compatible
- Supports 10/100/1000 Mbps half and full-duplex operation
- Backward compatible with USB 2.0 and 1.x devices
- Universal Power Adapter (NA/UK/EU) included

Hardware

Warranty 2 Years
USB-C Device Port(s) No

USB-C Host Connection No

Fast-Charge Port(s) No

Ports 3

Interface USB 3.0

USB 3.1 Gen 1

RJ45 (Gigabit Ethernet)

Bus Type USB 3.0

Industry Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3ab

IEEE 802.3az Energy-Efficient Ethernet, IEEE 802.3x Flow Control,

802.1q VLAN Tagging, 802.1p Layer 2 Priority Encoding



USB 3.0 - Backward compatible with USB 2.0 and 1.1

Chipset ID Genesys Logic - GL3522

ASIX - AX88179

Performance

Maximum Data Transfer

Rate

5 Gbps (USB 3.0)

2 Gbps (Ethernet; Full-Duplex)

Type and Rate USB 3.0 - 5 Gbit/s

Flow Control Full duplex flow control

Compatible Networks 10/100/1000 Mbps

Auto MDIX Yes

Full Duplex Support Yes

Jumbo Frame Support 4K max.

Connector(s)

Connector Type(s) USB Type-A (9 pin) USB 3.0 (5 Gbps)

RJ-45

USB Type-A (9 pin) USB 3.0 (5 Gbps)

Software

OS Compatibility Windows XP, Vista, 7, 8, 8.1, 10

Windows Server 2003, 2008 R2, 2012, 2012 R2, 2016, 2019

macOS 10.6 to 10.15

Chrome OS

Linux 2.6.x to 4.11.x <i>LTS versions only</i>

Special Notes / Requirements

System and Cable Requirements

Available USB 3.0 port

Note If connected to a USB 2.0 host port, performance may be limited

Indicators



LED Indicators Link

Activity

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC

Input Current 300 mA

Output Voltage 5 DC

Output Current 2 A

Center Tip Polarity Positive

Plug Type H

Power Consumption (In

Watts)

Environmental

Operating Temperature 0C to 50C (32F to 122F)

Storage Temperature -10C to 75C (14F to 167F)

Humidity 0~85% RH (Non-Condensing)

Physical Characteristics

Color Black

Form Factor Compact

Material Aluminum

Cable Length 5.8 in [14.8 cm]

Product Length 3.4 in [87 mm]

Product Width 1.7 in [43 mm]

Product Height 0.6 in [14 mm]

Weight of Product 2.2 oz [62 g]

Packaging Information



Package Quantity 1

Package Length 6.0 in [15.2 cm]

Package Width 8.5 in [21.7 cm]

Package Height 2.1 in [53 mm]

Shipping (Package)

Weight

13.2 oz [374 g]

What's in the Box

Included in Package

Aluminum USB 3.0 Hub w/ GbE Adapter

Universal Power Adapter (NA/JP, EU, UK, ANZ)

Driver CD

Instruction Manual

^{*}Product appearance and specifications are subject to change without notice.