

Dual-Slot M.2 Drive to SATA Adapter for 2.5" Drive Bay - RAID

Product ID: S322M225R



Boost your system performance by enhancing the capacity, speed and security of your data storage. This two-drive M.2 to SATA adapter lets you install two M.2 SATA drives instead of a SATA platter drive, in a single 2.5" drive bay, and increase your storage options by configuring a powerful RAID array.

The dual M.2 to SATA adapter supports multiple RAID modes, including RAID 0, 1, or spanning, helping you to achieve greater SSD capacity or data redundancy, depending on your selected RAID mode. The SSD adapter also supports non-RAID operation (JBOD) when paired with a port-multiplying SATA controller, so both drives can be used independently of one another.

The M.2 SATA SSD adapter lets you utilize the full potential of your SATA III controller. Using M.2 SATA SSDs in place of a platter drive reduces your data transfer bottlenecks, giving you file transfer speeds of up to 6Gbps.

The M.2 NGFF SATA RAID adapter also provides TRIM support to enhance the stability and performance of your M.2 NGFF SSDs.

This open-frame adapter is easy to install as it comes with all the necessary installation hardware and doesn't require any extra software or drivers, to get you up and running quickly.

The S322M225R is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Take advantage of the speed of M.2 drives in any 2.5" SATA application
- · Add data redundancy to your system or increase the storage capacity of your system through RAID



- Retrieve or back up data from M.2 (NGFF) drives using a standard SATA interface
- Access M.2 (NGFF) drives from an external source, such as a SATA drive enclosure or docking station

Features

- Install two M.2 SSD drives into a single 2.5" drive bay
- Multiple RAID modes supported: RAID 0, 1, spanning, or JBOD
- Open-frame steel mounting bracket with 2.5" SATA form factor housing
- Supports 7 mm or larger 2.5" SATA bays
- Supports B key M.2 SATA SSDs full-length M.2 drives (2230, 2242, 2260, 2280)
- Not compatible with M.2 NVMe or AHCI PCI-Express SSDs
- Supports SATA I, II and III (up to 6Gbps)
- TRIM support to enhance the stability and performance of your M.2 NGFF SSDs
- SMART support
- Easy to install with all necessary hardware included

Hardware		
	Warranty	2 Years
	Interface	SATA
	Number of Drives	2
	Compatible Drive Types	M.2 (SATA, B-Key, NGFF)
	Drive Installation	Fixed
	Supported Drive Height(s)	2230
		2242
		2260
		2280
	Chipset ID	ASMedia - ASM1092R

Performance

Maximum Data Transfer 6 Gbps



Rate

TRIM Support Yes

S.M.A.R.T. Support Yes

Type and Rate SATA III (6 Gbps)

Port Multiplier Yes

Hardware Raid Supported Yes

Supported RAID Modes RAID 0 (Striped Disks)

RAID 1 (Mirrored Disks)

JBOD - (Just a Bunch of Disks)

BIG (Spanning or Concatenation)

Hot Swap Capability No

General Specifications Not compatible with M.2 NVMe or AHCI PCI-Express SSDs

In order to see multiple drives in JBOD mode, your computer's

SATA controller must also support Port Multiplier.

Connector(s)

Drive Connectors M.2 (SATA, B-Key, NGFF)

Host Connectors SATA Data & Power Combo (7+15 pin)

Software

OS Compatibility OS independent; No software or drivers required

Special Notes / Requirements

Note TRIM and SMART have limited support while in a RAID

configuration. A SATA controller with Port Multiplier support is required, in addition to the product configured in JBOD mode, to

provide full TRIM and SMART support.

Environmental

Operating Temperature +5C to +50C (+41F to +122F)

Storage Temperature -25C to +70C (-13F to +158F)

Humidity 15% to 90%



Physical Characteristics

Color Red

Material Steel

Product Length 3.9 in [100 mm]

Product Width 2.8 in [70 mm]

Product Height 0.3 in [7 mm]

Weight of Product 1.4 oz [41 g]

Packaging Information

Package Length 5.6 in [14.2 cm]

Package Width 6.8 in [17.2 cm]

Package Height 1.2 in [30 mm]

Shipping (Package)

Weight

3.9 oz [110 g]

What's in the Box

Included in Package dual M.2 to SATA host adapter

sets of drive-mounting hardware

adapter-mounting screws

quick-start guide

^{*}Product appearance and specifications are subject to change without notice.