

Hard Drive Enclosure for 3.5in SATA Drives - USB 3.0

Product ID: S3510SMU33



The S3510SMU33 USB 3.0 hard drive enclosure enables you to connect a 3.5in SATA hard drive through an available USB port.

With support for UASP, the enclosure performs up to 70% faster than conventional USB 3.0, when paired with a UASP-enabled host controller to utilize the full potential of your SATA III hard drives. See our UASP testing results below for further details.

The HDD enclosure offers a versatile solution for increasing the storage/backup capabilities of your computer, with support for SATA I/II/III hard drives at capacities of up to 4TB. Plus, the enclosure features high-quality aluminum construction and a stylish silver design that looks great in any application.

To ensure compatibility with your computer system, the S3510SMU33 supports all of the leading operating systems, including: Windows, OSX, Linux and Google Chrome.

The S3510SMU33 USB 3.0 HDD enclosure is backed by a 2-year StarTech.com warranty and free lifetime technical support.

UASP is supported in Windows 8, Mac OSX (10.8 or above), and Linux. In testing UASP performs with a 70% faster read speed and 40% faster write speed over traditional USB 3.0 at peak performance.

At the same peak in testing UASP also shows an 80% reduction in required processor resources.

Testing results were obtained using an Intel Ivy Bridge system, a UASP enabled StarTech.com Enclosure, and a SATA III solid state drive.

Certifications, Reports and Compatibility

Applications

- Take advantage of new laptops and desktops with USB 3.0 (UASP) connectivity
- Turn a high capacity SATA hard drive into portable, external storage
- Create a fast, portable external storage solution for desktops, laptops or ultrabooks
- Upgrade from a USB 2.0 drive enclosure to faster USB 3.0
- Add on extra storage to almost any USB-enabled computer system
- Share large files between computers quickly and securely without a network
- Retrieve data from an old SATA drive, or turn the unused drive into additional external storage space

Features

- Compliant with USB Attached SCSI Protocol (UASP) Transport Specifications
- Lightweight and durable aluminum enclosure
- SuperSpeed USB 3.0 compliant host interface supporting data transfer rates up to 5Gbps
- Backward compatible with high Speed USB 2.0 host interface, with transfer rates up to 480Mbps
- Power/Activity LED indicator
- Compatible with SATA revision I/II/III (1.5/3.0/6.0 Gbps) drives
- Plug-and-Play and Hot-Swap compatible

Hardware

| | |
|------------------------|--------------------|
| Warranty | 2 Years |
| Fan(s) | No |
| Interface | USB 3.0 |
| Number of Drives | 1 |
| Drive Size | 3.5in |
| Compatible Drive Types | SATA |
| Drive Installation | Fixed |
| Chipset ID | ASMedia - ASM1153E |

Performance



| | |
|-------------------------|---|
| Type and Rate | USB 3.0 - 5 Gbit/s |
| UASP Support | Yes |
| Type and Rate | SATA III (6 Gbps) |
| Hardware Raid Supported | No |
| Max Drive Capacity | No maximum currently known; tested with up to 14TB 7200 RPM hard drive. |

Connector(s)

| | |
|------------------|------------------------------------|
| Drive Connectors | SATA Data & Power Combo (7+15 pin) |
| Host Connectors | USB Type-B (9 pin) USB 3.0 |

Software

| | |
|------------------|---|
| OS Compatibility | OS independent; No software or drivers required |
|------------------|---|

Special Notes / Requirements

| | |
|-------------------------------|--------------------|
| System and Cable Requirements | Available USB port |
|-------------------------------|--------------------|

Indicators

| | |
|----------------|------------------|
| LED Indicators | Power & Activity |
|----------------|------------------|

Power

| | |
|------------------------------|---------------------|
| Power Source | AC Adapter Included |
| Input Voltage | 100 - 240 AC |
| Input Current | 0.6 A |
| Output Voltage | 12V DC |
| Output Current | 2 A |
| Center Tip Polarity | Positive |
| Power Consumption (In Watts) | 24 |

Environmental

| | |
|-----------------------|---------------------------|
| Operating Temperature | 0C to 40C (32F to 104F) |
| Storage Temperature | -10C to 65C (14F to 149F) |



| | |
|----------|---|
| Humidity | Operation Humidity: 10% ~ 90% RH Storage Humidity: 5% ~ 95% RH |
|----------|---|

Physical Characteristics

| | |
|-------------------|----------------------|
| Color | Silver |
| Material | Aluminum and Plastic |
| Product Length | 7.5 in [19.2 cm] |
| Product Width | 1.2 in [31.4 mm] |
| Product Height | 4.5 in [11.5 cm] |
| Weight of Product | 11.3 oz [321 g] |

Packaging Information

| | |
|---------------------------|------------------|
| Package Length | 8.7 in [22 cm] |
| Package Width | 5.3 in [13.5 cm] |
| Package Height | 4.2 in [10.6 cm] |
| Shipping (Package) Weight | 28.1 oz [797 g] |

What's in the Box

| | |
|---------------------|--|
| Included in Package | 3.5" USB 3.0 SATA III HDD Enclosure Screw Kit Universal Power Adapter (NA/JP / UK / EU / ANZ) USB 3.0 Cable (1m) HDD Stand Product Manual |
|---------------------|--|

****Product appearance and specifications are subject to change without notice.***

