

## 1-Port Gigabit Ethernet Network Card - PCI Express, Intel I210 NIC

Product ID: ST1000SPEXI



Boost the performance and capabilities of your server or desktop computer by adding a Gigabit Ethernet port through a PCI Express slot. This GbE (Gigabit Ethernet) network card makes it easy to create a high-performance, cost-effective networking solution.

This PCI Express Gigabit Ethernet card utilizes the Intel I210-AT chipset, delivering the power, performance and enhanced capabilities you need for dependable network connections to your server or computer. Compliant with IEEE 802.3/u/ab standards, the GbE network card provides an effective upgrade or replacement network port, with a maximum throughput of up to 1000Mbps in each direction (2000 Mbps total) - up to ten times faster than 10/100 Ethernet.

The I210 chipset provides many advanced features to support load-balancing the flow of network traffic, to enhance throughput and provide greater data reliability. It also supports Audio-Video Bridging (AVB) to enable tightly controlled media stream synchronization, buffering and resource reservation.

Compatible with a broad range of operating systems, this versatile PCIe Gigabit NIC is ideal for many business applications requiring servers or workstation upgrades. It's a cost-effective way to upgrade your server or computer from a 10/100 Ethernet port to a Gigabit Ethernet port, or add an Ethernet port to take advantage of advanced features such as VLAN tagging, Jumbo Frames, Wake-On-LAN and Auto MDIX.

With a dual-profile design, the PCI Express network card installs easily into a wide range of computer/server chassis, regardless of form factor. The card comes equipped with a full-sized bracket, and includes a low-profile/half-height installation bracket that you can use as needed.

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that works with a wide range of IT connectivity accessories. The software suite includes:

Mac Address Pass-Through Utility: To improve network security.

Wi-Fi Auto Switch Utility: Enabling users to quickly access faster network speeds via wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.StarTech.com/Connectivity-Tools



The ST1000SPEXI is backed by a StarTech.com 2-year warranty and free lifetime technical support.

## **Certifications, Reports and Compatibility**

## **Applications**

- Upgrades to servers or workstations in need of enhanced performance, advanced features and greater reliability
- Upgrade a 10/100 Ethernet port on your computer to GbE network capability
- Add GbE networking capabilities to an old system that doesn't have an Ethernet port
- Add an additional Ethernet port to a workstation or server computer for redundancy

## **Features**

- Add a 10/100/1000 RJ-45 Ethernet port to a client, server or desktop through one PCIe slot
- Intel I210-AT chipset
- PXE network boot
- Fully compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- Auto MDIX support
- Autonegotiation support
- Wake-on-LAN support
- Up to 9K jumbo frame support
- IEEE802.3az Energy Efficient Ethernet (EEE)
- Supports IEEE 802.1Q VLAN tagging
- Supports Audio-Video Bridging
- Full or low-profile (LP bracket included) installation
- Full duplex support
- STARTECH.COM CONNECTIVITY TOOLS: Provided with this device, the application improves performance and security, featuring MAC Address Changer & Wi-Fi Auto Switch utilities

**Hardware** 



Warranty 2 Years

Ports 1

Bus Type PCI Express

Card Type Standard Profile (LP bracket incl.)

Industry Standards IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE

802.3ab 1000BASE-T

IEEE 802.1Q VLAN Tagging

IEEE 802.3x Full Duplex Flow Control

Chipset ID Intel - I210-AT

**Performance** 

Maximum Data Transfer

Rate

2000 Mbps (full-duplex)

Compatible Networks

10/100/1000 Mbps

Auto MDIX

Yes

Full Duplex Support

Yes

Jumbo Frame Support

9K max.

Promiscuous Mode

Yes

Supported Protocols

IEEE 802.3ad (link aggregation), IEEE 1588 (time sync)

Connector(s)

Connector Type(s)

PCI Express x1

RJ-45

**Software** 

OS Compatibility Windows 7, 8, 8.1, 10, 11

Windows Server 2008 R2, 2012 R2, 2016, 2019

Linux 2.4.x to 4.11.x <i>LTS versions only</i>

Special Notes / Requirements

System and Cable Requirements

Available PCI Express expansion card slot



**Indicators** 

LED Indicators 100/1000 Mbps Indicator

Link/Activity

**Power** 

Power Consumption (In Watts)

Max 0.8W

**Environmental** 

Operating Temperature 5C to 50C (41F to 122F)

Storage Temperature -20C to 60C (-4F to 140F)

Humidity 20% ~ 80% RH

Physical Characteristics

Color Black

Material Steel

Product Length 4.7 in [12 cm]

Product Width 2.6 in [66 mm]

Product Height 0.7 in [18 mm]

Weight of Product 1.3 oz [38 g]

Packaging Information

Package Length 6.7 in [17 cm]

Package Width 5.6 in [14.2 cm]

Package Height 1.1 in [28 mm]

Shipping (Package)

Weight

3.5 oz [100 g]

What's in the Box

Included in Package 1 Port Network Card

Low Profile Bracket

Instruction Manual



\*Product appearance and specifications are subject to change without notice.