

16 Port 1U Rackmount USB KVM Switch Kit with OSD and Cables

Product ID: SV1631DUSBUK



The SV1631DUSBUK 16 Port 1U Rack Mount USB KVM Switch Kit with OSD and Cables offers a well-appointed KVM switch that includes all of the cables and accessories required to connect to 16 servers or PCs right out of the box, making setup convenient and simple.

The USB KVM delivers a dependable computer management tool that allows you to control up to 16 USB-connected computers from a single keyboard, mouse and display, providing maximum control through hotkey command-based switching or front panel push-buttons, with the added configurability and convenience of an On-Screen Display.

A suitable addition to server room operations, the 16-port switch can be rackmounted into 1U of cabinet space and can be cascaded with multiple KVM switches to enable control of up to 136 computers from this single switch.

This product is TAA compliant and backed by a Startech.com 3-year warranty with free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Effectively manage your server farms from a single console
- Useful in Software QA labs where testing is being done across multiple platforms
- Great for PC test/burn-in computer control, avoiding the cost of buying additional peripherals
- Central control for multiple systems in a Datacenter
- Systems management in Co-location/ISP facilities
- Manufacturing line computer control and management



Features

- Package includes 16x 6ft USB KVM cables
- USB Keyboard and Mouse combo supported on 1 USB connection
- OSD security option allows selected KVM ports to be password-protected from unauthorized use
- Auto-scan function automatically switches between connected PCs sequentially
- Cascade configuration expands system capability
- Hotkey functions allow easy computer access
- Identifies and selects computers by the names assigned

Resolutions

• Plug-and-play system configuration

Hardware		
	Warranty	3 Years
	Audio	No
	KVM Ports	16
	PC Interface	USB
	PC Video Type	VGA
	Number of Monitors Supported	1
	Rack-Mountable	Yes
	Cables Included	Yes
	Daisy-Chain	Yes
Performance	_	
	On-Screen Display	Yes
	IP Control	No
	Hot-Key Selection	Yes
	Maximum Analog	1920 x 1440@60Hz (1920 x 1200@60Hz



Wide Screen Supported Yes

Maximum Number of Users

1

Maximum Cascaded

Computers

136

Port Selection Support

Push Button, Hotkeys, and OSD (On Screen Display)

MTBF

158000 hours

Connector(s)

Console Interface(s) USB Type-A (4 pin) USB 2.0

VGA (15 pin, High Density D-Sub)

Host Connectors VGA (15 pin, High Density D-Sub)

Software

OS Compatibility OS independent; No software or drivers required

Indicators

LED Indicators Green - PC Online

Green - Power

Red - PC Selected

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC

Output Voltage 9V DC

Output Current 1A

Center Tip Polarity Positive

Power Consumption (In

Watts)

9

Environmental

Operating Temperature 5°C to 40C (41F to 104F)

Storage Temperature -20°C to 60C (-4F to 140F)



	Humidity	0~80% RH
Physical Characteristics		
	Color	Black
	Material	Steel
	Product Width	17.3 in [44 cm]
	Product Height	1.8 in [45 mm]
	Product Depth	7.5 in [19 cm]
	Weight of Product	5.3 lb [2.4 kg]
Packaging Information		
	Package Length	23.3 in [59.3 cm]
	Package Width	10.4 in [26.3 cm]
	Package Height	4.7 in [12 cm]
	Shipping (Package) Weight	13.4 lb [6.1 kg]
What's in the Box		
	Included in Package	16-port USB KVM switch
		mounting brackets
		6ft 2-in-1 USB VGA KVM cables
		screw kit
		foot pads
		universal power adapter (NA/EU/UK/AU)
		instruction manual

^{*}Product appearance and specifications are subject to change without notice.