

## 4 Port DVI VGA Dual Monitor KVM Switch USB with Audio & USB 2.0 Hub

**Product ID:** SV431DDVDUA



The SV431DDVDUA 4-port DVI VGA dual monitor KVM switch lets you control 4 Dual Display computers using a single USB mouse and keyboard peripheral set.

This dual view KVM switch provides 1 VGA and 1 DVI-I port per computer connection for high-resolution video, as well as audio switching capability between connected computers.

The DVI/VGA KVM switch features an integrated 2-port USB hub that allows USB 2.0 peripherals to be shared between connected computers, and offers a compact design with a rugged metal chassis for durable performance.

NOTE: While both DVI-I (analog) and DVI-D (digital) are supported by the KVM, source PCs must output the same signal for proper switching. It is recommended wherever possible to use DVI-D cables across all PC to KVM and KVM to Console connections. If necessary, please contact technical support for assistance identifying your source.

This product is TAA compliant and backed by a Startech.com 3-year warranty with free lifetime technical support.

If you'd like to mount this KVM switch to your server rack, StarTech.com offers a 1U Rackmount Bracket (sold separately) that turns this KVM into a rackmountable KVM.

## Certifications, Reports and Compatibility

### Applications

- Perfect solution for desktops, workstations and servers with both VGA and DVI-digital ports, allowing a user to take advantage of dual monitor configurations
- Ideal for financial/banking industries, graphic designers, engineers, multi-media designers, and industries using CAD/CAM applications, where high resolution dual monitor units are needed

- Suitable for use in environments with electromagnetic interference, based on sturdy metal design
- Versatile support for setups where one machine is DVI & VGA, and the other is VGA & VGA (with available adapters)

## Features

- Direct channel selection and operation using front panel push-button or keyboard hotkeys
- Supports a maximum digital resolution of 1920 x 1200 and analog of 1920 x 1440; Recommended resolution is 1920 x 1200
- OS independent (no drivers or software required)
- Independent or simultaneous audio switching
- Full support for plug-n-play peripherals
- Rugged, all-metal chassis for use in harsh environments
- Status LED display for easy port status monitoring
- USB style keyboard and mouse, plus two other USB 2.0 peripherals can be shared between up to two computers
- Tone indicator for computer switching
- Selectable time intervals for auto scan
- Rear function key to adjust video strength
- HDCP compliant
- Support DDC2B emulation and EDID pass through, which allows the display adapter to recognize and auto configure screens to match the display capabilities
- Supports Dual Monitor/Flat Panel Displays [1 x DVI + 1 x VGA]

---

### Hardware

Warranty	3 Years
Audio	Yes
KVM Ports	4
PC Interface	USB
PC Video Type	DVI+VGA
Number of Monitors Supported	Yes

Rack-Mountable            Optional

Cables Included            No

Daisy-Chain                No

**Performance**

On-Screen Display        No

DVI Support                Yes - Single Link

IP Control                 No

Hot-Key Selection        Yes

Maximum Analog  
Resolutions                1920 x 1400

Maximum Digital  
Resolutions                1920 x 1200

Maximum Number of  
Users                        1

Port Selection Support    Push Button and Hotkeys

MTBF                        140000 hours

**Connector(s)**

Console Interface(s)     3.5 mm Mini-Jack (3 Position)

DVI-I (29 pin)

USB Type-A (4 pin) USB 2.0

VGA (15 pin, High Density D-Sub)

Host Connectors         3.5 mm Mini-Jack (3 Position)

DVI-I (29 pin)

USB B (4 pin)

VGA (15 pin, High Density D-Sub)

**Software**

OS Compatibility         OS independent; No software or drivers required



**Special Notes / Requirements**

Note	While both DVI-I (analog mode) and DVI-D (digital only) are supported by the KVM, both source PCs must output the same signal type for proper switching. It is recommended wherever possible to use DVI-D cables across all PC to KVM and KVM to Console connections. Please contact technical support for assistance identifying your source.
------	--

---

**Indicators**

LED Indicators	Green - PC Detected
	Green - Power
	Red - PC Indicator

---

**Power**

Power Source	AC Adapter Included
Input Voltage	100 - 240 AC
Input Current	0.8A
Output Voltage	12V DC
Output Current	1.5A
Center Tip Polarity	Positive
Plug Type	M
Power Consumption (In Watts)	18

---

**Environmental**

Operating Temperature	0C to 40C (32F to 104F)
Storage Temperature	-20C to 60C (-4F to 140F)
Humidity	80% RH

---

**Physical Characteristics**

Color	Black
Material	Steel
Product Length	6.4 in [16.3 cm]
Product Width	8.7 in [22 cm]



Product Height	2.4 in [60 mm]
Product Depth	5.1 in [13 cm]
Weight of Product	2.8 lb [1.3 kg]

---

**Packaging Information**

Package Length	9.8 in [24.9 cm]
Package Width	11.6 in [29.5 cm]
Package Height	3.4 in [86 mm]
Shipping (Package) Weight	3.9 lb [1.8 kg]

---

**What's in the Box**

Included in Package	4-port KVM switch
	foot pads
	universal power adapter (NA/EU/UK/AU)
	instruction manual

---

***\*Product appearance and specifications are subject to change without notice.***

