



### Key Features


- Self wiping contacts
- Slow make & break
- Momentary action
- Choice of switch circuits
- Choice of actuators

### Approvals and specifications

In house test:  
0.5A 250Vac T85 — Indicative rating only


### Dimensions

Dimensions (mm) Nylon S and L actuators



Neck thread - 40 TPI Whit. Actuator travel - 2.5 max

**Stainless steel V actuator (IP66)**



Neck thread - 26 TPI Whit. Actuator travel - 2.5 max

Terminal	Function	Actuator	Body Code	Options
T	<p><b>0916</b>              Black base            SP ON - OFF (momentary)</p> <p><b>0917 50V only</b>              Brown base            SP ON - OFF (momentary 1 side)</p> <p><b>0918</b>              White base            SP ON - OFF (momentary OFF)</p> <p><b>0919</b>              Black base            DP ON - OFF (momentary 1 side)</p> <p><b>0920</b>              White base            DP ON - OFF (momentary ON)</p>	<p><b>S</b>            Small Actuator  </p> <p><b>L</b>            Large Actuator  </p> <p><b>V</b>            Vandal Resistant IP66 Flat-top Stainless Steel  </p>	<p></p> <p><b>7.1</b></p> <p>Panel Cut-out (L &amp; S Actuators)</p> <p>Panel thickness Both nuts - 2.5mm            No Backnut - 4.0</p> <p>Panel Cut-out (Stainless Steel V Actuator)            Panel thickness - 8.0mm</p>	<p>Finish            Gloss finish for L and S actuators.</p> <p>Colour            Call sales for custom colours.            A full range is available for large orders.</p>