



25	09 47 47 47 125	4x2AWG 27/7 S/FTP Cat.6 PUR	30,0 (±0,300) m
24	09 47 47 47 123	4x2AWG 27/7 S/FTP Cat.6 PUR	20,0 (±0,200) m
23	09 47 47 47 124	4x2AWG 27/7 S/FTP Cat.6 PUR	16,0 (±0,160) m
22	09 47 47 47 122	4x2AWG 27/7 S/FTP Cat.6 PUR	15,0 (±0,150) m
21	09 47 47 47 121	4x2AWG 27/7 S/FTP Cat.6 PUR	10,0 (±0,100) m
20	09 47 47 47 120	4x2AWG 27/7 S/FTP Cat.6 PUR	9,0 (±0,090) m
19	09 47 47 47 119	4x2AWG 27/7 S/FTP Cat.6 PUR	8,0 (±0,080) m
18	09 47 47 47 118	4x2AWG 27/7 S/FTP Cat.6 PUR	7,5 (±0,075) m
17	09 47 47 47 117	4x2AWG 27/7 S/FTP Cat.6 PUR	7,0 (±0,070) m
16	09 47 47 47 116	4x2AWG 27/7 S/FTP Cat.6 PUR	6,0 (±0,060) m
15	09 47 47 47 115	4x2AWG 27/7 S/FTP Cat.6 PUR	5,0 (±0,040) m
14	09 47 47 47 114	4x2AWG 27/7 S/FTP Cat.6 PUR	4,0 (±0,040) m
13	09 47 47 47 113	4x2AWG 27/7 S/FTP Cat.6 PUR	3,0 (±0,040) m
12	09 47 47 47 112	4x2AWG 27/7 S/FTP Cat.6 PUR	2,5 (±0,040) m
11	09 47 47 47 111	4x2AWG 27/7 S/FTP Cat.6 PUR	2,0 (±0,040) m
10	09 47 47 47 110	4x2AWG 27/7 S/FTP Cat.6 PUR	1,5 (±0,040) m
9	09 47 47 47 109	4x2AWG 27/7 S/FTP Cat.6 PUR	1,0 (±0,040) m
8	09 47 47 47 108	4x2AWG 27/7 S/FTP Cat.6 PUR	0,9 (±0,040) m
7	09 47 47 47 107	4x2AWG 27/7 S/FTP Cat.6 PUR	0,8 (±0,040) m
6	09 47 47 47 106	4x2AWG 27/7 S/FTP Cat.6 PUR	0,7 (±0,040) m
5	09 47 47 47 105	4x2AWG 27/7 S/FTP Cat.6 PUR	0,6 (±0,040) m
4	09 47 47 47 104	4x2AWG 27/7 S/FTP Cat.6 PUR	0,5 (±0,020) m
3	09 47 47 47 103	4x2AWG 27/7 S/FTP Cat.6 PUR	0,4 (±0,020) m
2	09 47 47 47 102	4x2AWG 27/7 S/FTP Cat.6 PUR	0,3 (±0,020) m
1	09 47 47 47 101	4x2AWG 27/7 S/FTP Cat.6 PUR	0,2 (±0,020) m

Cont. no.	Part-No.	Type of cable	Dim. a
-----------	----------	---------------	--------

For lengths < 1,0m:
 - relative positioning of the connectors to each other will be as presented in the drawing, however with an admissible angular deviation around cable axis of $\pm 30^\circ$
 For lengths $\geq 1,0m$:
 -relative positioning of the connectors to each other not obligatory
 -Transmission properties in accordance with IEC 61935-2 Cat.6
 -Protection level: IP20

For Information Only
 -won't be replaced when changed-

	All Dimensions in mm Original Size DIN A 3			Techn. Character.			Nicht tolerierte Maß/Free size tolerances		
DRS435G	02.02.12	RO	Detail.	14.11.08	MR	Maßstab/Scale 2:1	RJ45 cord, 2xRJ45 overmoulded, 4x2xAWG 27/7, Cat.6, PUR, 1:1		
DRS435F	14.02.11	RO	Insp.	14.11.08	RA				
DRS435D	19.03.10	RA	Stand.						
35587	16.12.08	MR	HARTING Electronics GmbH & Co. KG				TB 09 47 47 47 1xx		Blatt/ page
35043			D-32339 ESPELKAMP						
Mod.	Dat.	Name					Sub.		

Alle Rechte vorbehalten/ All rights reserved