

Modular test probes (for use with modular test leads)

Using modular test leads, this wide variety of test probes allows the configuration of leads for a wide variety of needs, whether industrial, electrical, or electronic.



TP175


TP175 TwistGuard™ Test Probes

- Modular test probes of the popular TL175 Test Leads (page 6)
- Patented extendable tip guard meets CAT III 1000 V, CAT IV 600 V requirements while providing the flexibility you need for CAT II measurements
- 2 mm (0.08 in) diameter stainless steel probe tips

TP220 SureGrip™ Industrial Test Probes

One pair (red, black) industrial test probes with stainless steel tip.

- Sharp, 12 mm (0.47 in) tips
- Safety rating: CAT II 1000 V (CAT III 1000 V, CAT IV 600 V with protective cap), 10 A



TP220

TP1 Slim Reach™ Test Probes

One pair (red, black) slender probes with flat stainless steel blade to hold securely in blade-type electrical wall sockets.

- Tip length up to 14.7 mm (0.58 in)
- Safety rating: CAT II 1000 V, 10 A (CAT III 1000 V, CAT IV 600 V with protective cap)

TP2 Slim Reach™ Test Probes

One pair (red, black) slender stainless steel probes for accessing closely-spaced or recessed terminals such as in electronic environments.

- 2 mm (0.08 in) diameter tip
- Safety rating: CAT II 1000 V, 10 A (CAT III 1000 V, CAT IV 600 V with protective cap)

TP4 Slim Reach™ Test Probes

One pair (red, black) slender stainless steel probes for accessing closely-spaced or recessed electrical terminals.

- 4 mm (0.16 in) diameter probe tip designed to fit securely into IEC (C13 and C14) electrical wall outlets
- Safety rating: CAT II 1000 V, 10 A



TP74



TP38

TP80 Electronic Test Probes

One pair (red, black) electronics test probes.

- IC-insulated cap prevents shortening of IC legs for probing high density components or boards
- Tip length up to 3.9 mm (0.157 in)
- Tip diameter: 1 mm (0.04 in)
- Safety rating: CAT III 1000 V, 1 A

TP74 Lantern Tip Test Probes


One pair (red, black) featuring nickel-plated brass ends.

- Banana-style 4 mm (0.16 in) spring contacts
- Safety rating: CAT II 1000 V, 10 A (CAT III 1000 V, CAT IV 600 V with protective cap)


TP38 Slim Reach™ Test Probes

One pair (red, black) slender stainless steel probes for accessing closely-spaced or recessed terminals.

- Tip length: 24 mm (0.95 in) which includes the insulated part of the tip
- Probe tip insulated to 4 mm (0.16 in) from the end
- Safety rating: CAT IV 600 V, CAT III 1000 V, 10 A



TP1



TP2



TP4



TP80