



Thermal transfer ribbons for heat shrink and Tiptags

TTDTHOUT – Smudge, Scratch, Oil, Benzene and Alcoholic Solvent Resistant


The TTDTHOUT ribbon consists of a special resin composition. In combination with our identification materials the printing is high resistant against high temperatures, scratches and chemicals. The thermal transfer print technology is based on heating up certain dots in the print head. This transfers the ink very precisely from the ribbon onto the surface of the printed material.

Features and benefits

- Thermal transfer ribbons for high quality print results on heat shrink tubing and Tiptag identification tags
- Ribbons are specifically designed to maximize print performance for the recommended material



Ribbons for printing on tubing and Tiptags.



ID: The standard inside core diameter is 25.4 mm.

TYPE	Recommended Material	Colour	Width (W)	Reel Length	Article-No.
TTDTHOUT 40MM	TCGT/TULT(DS)/TLFX(DS)/TDRT(DS)/TLFD DS/TIPTAG	Black (BK)	40.0	300 m	556-00139
TTDTHOUT 60MM	TCGT/TULT(DS)/TLFX(DS)/TDRT(DS)/TLFD DS/TIPTAG	Black (BK)	60.0	300 m	556-00140
TTDTHOUT 100MM	TCGT/TULT(DS)/TLFX(DS)/TDRT(DS)/TLFD DS/TIPTAG	Black (BK)	100.0	300 m	556-00141

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

