



## 4-port Hub **HUB2**

Ideal for use with today's Ultrabooks and thin-and-light laptops, Transcend's SuperSpeed USB 3.1 Gen 1 Hub transforms a single USB 3.1 Gen 1 port into four, instantly expanding the number of high-performance USB 3.1 Gen 1 devices you can connect to your computer at the same time. As it is USB bus powered with the cable attached, no extra power adapter is needed. Plus, the ultra slim and portable design allows you to transfer files wherever you go.



### **SuperSpeed USB 3.1 Gen 1 interface**

Compliant with the SuperSpeed USB 3.1 Gen 1 specification, Transcend's HUB2 provides data transfer rates up to 10 times faster than USB 2.0, allowing you to enjoy fast and efficient data transfer.



### **Transforms a single USB 3.1 Gen 1 port into four**

Transcend's HUB2 transforms a single port into four, instantly expanding the number of devices that you can connect to your computer at one time. It's perfect for Ultrabooks and thin-and-light notebooks that lack many USB 3.1 Gen 1 ports.



### **USB powered with cable attached**

HUB2 is USB bus powered with cable attached, thus no extra power adapter is needed. Simply connect your devices to HUB2 to instantly open and view your files. The small and compact design allows you to carry it around easily without adding any extra burden, ideal for travel and business trip.



## 4-port Hub HUB2

### Features

- USB 3.1 Gen 1 interface
- Up to 10x faster than USB 2.0
- Supports USB powered, no extra power adapter needed
- Comes with 4 USB 3.1 Gen 1 ports and USB cable attached
- Compact and portable design

### Specifications

#### Appearance

|            |   |
|------------|---|
| Dimensions | 73.8 mm x 37.2 mm x 10.4 mm (2.91" x 1.46" x 0.41") |
|------------|---|

|        |                |
|--------|----------------|
| Weight | 29 g (1.02 oz) |
|--------|----------------|

#### Interface

|                      |               |
|----------------------|---------------|
| Connection Interface | USB 3.1 Gen 1 |
|----------------------|---------------|

#### Operating Environment

|                       |                           |
|-----------------------|---------------------------|
| Operating Temperature | 0°C (32°F) ~ 70°C (158°F) |
|-----------------------|---------------------------|

#### Power

|              |                         |
|--------------|-------------------------|
| Power Supply | 5V / 0.9A from USB port |
|--------------|-------------------------|

#### Warranty

|             |                        |
|-------------|------------------------|
| Certificate | CE/FCC/BSMI/KC/RCM/EAC |
|-------------|------------------------|

|          |                           |
|----------|---------------------------|
| Warranty | Two-year Limited Warranty |
|----------|---------------------------|

#### System Requirement

|                  |  |
|------------------|--|
| Operating System | Microsoft Windows 7<br>Microsoft Windows 8<br>Microsoft Windows 10<br>Mac OS X 10.2.8 or later<br>Linux Kernel 2.6.30 or later |
|------------------|--|

### Ordering Information

|          |
|----------|
| TS-HUB2K |
|----------|